

PAR38 LED Single Optic Lamps with AirFlux Technology

13PAR38/F25 2700 DIM AF SO 6/1

Philips PAR38 LED Single Optic Lamps with AirFlux Technology improves shopping experience with superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.

Product data

• General Characteristics

Cap-Base PAR38 [PAR38 mm] Bulb 45000 hr

Rated Avg. Life

(Hours) Rated Lifetime (years)

41.1 an

• Light Technical Characteristics

Color Code ww Color Designation Warm White Beam Angle 25 D

Beam Description 25D [Medium beam]

Correlated Color 2700 K

Temperature

Approximate Lumens 900 Lm Approx. MBCP 5300 cd CRI 69.23 Lm/W Luminous Efficacy

Lamp

Color Temp. (Kelvin) 2700 K [CCT 2700K]

Rated Luminous Flux 900 Lm

• Electrical Characteristics

13 W Wattage Wattage Technical 13 W 120 V Voltage

Warnings and Safety

• Suitable for use in damp locations.

Line Frequency 60 Hz Power Factor 0.9 -Lamp Current mA 126 mA Dimmable Yes 100 W Wattage Equivalent Starting Time 0.5 s

Measuring Conditions

Switching cycle 20000x

• Product Dimensions

Overall Length C 130 mm Diameter D 120 mm

• Product Data

Product number 430066 Full product name 13PAR38/F25 2700 DIM AF SO 6/1 13PAR38/F25 2700 DIM AF RO 6/1 Short product name

Pieces per Sku eop_pck_cfg Skus/Case

Bar code on pack 46677430061 50046677430066 Bar code on case 929000252204 Logistics code(s) eop_net_weight_pp 0.370 kg


• Not for use in totally enclosed luminaires.





PAR38 LED Single Optic Lamps with AirFlux Technology

Dimensional drawing



13PAR38/F25 2700 DIM AF SO 6/1

Product	C (Norm)	C1 (Max)	D (Norm)	D1 (Norm)
LED 13W E26 2700K PAR38 25D DIM	130	-	120	-



E26



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.