BCFL42



| eplacement Fluorescent Ballasts. | luct | Project: | | Туре: | |
|----------------------------------|-----------------|------------------------|------------|---------------|-------------|
| Color: N/A | Weight: 0.7 lbs | | | | |
| | | Prepared By | | Date: | |
| | | Lamp Info | | Ballast Info | |
| | | Type: | 42W Triple | Type: | Elec HPF QT |
| | | Watts: | 42W | 120V: | 0.38A |
| | | Shape/Size: | N/A | 208V: | 0.3A |
| | | Base: | N/A | 240V: | 0.2A |
| | | ANSI: | N/A | 277V: | 0.17A |
| | | | N/A | Input Watts: | 46W |
| | | Hours: | IN/A | input vvalis. | 4000 |
| | | Hours: Lamp Lumens: | N/A | Efficiency: | 91% |

Technical Specifications

Electrical

Ballast Volts:

120-277 volt.

Other

Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

Construction

Ballast Minimum Starting Temperature:

0°F.