



The affordable LED GUS is designed to deliver general ambient lighting for surface-mount ceiling/wall or pendant mount applications. Diffusion lens delivers improved visual performance and a more refined look. Replaces traditional 4' linear fluorescent wraparound fixtures.

Color: White

Weight: 9.0 lbs

Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type:	Constant Current	Watts:	40W
120V:	0.34A	Color Temp:	N/A
208V:	0.21A	Color Accuracy:	N/A
240V:	0.19A	L70 Lifespan:	N/A
277V:	0.15A	Lumens:	4662
Input Watts:	40W	Efficacy:	116 LPW
Efficiency:	99%		

Technical Specifications

Lightcloud

Lightcloud Controller Installed:

Fixture, Zone, and plug-load control from one powerful device. Capable of switching, 0-10V dimming, power monitoring. Can also be used to extend the range of the Lightcloud mesh network. Attach to fixture, junction box, or electrical panel.

Listings

UL Listing:

Suitable for damp locations

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.

DLC Product Code: PL280Q05

Electrical

Driver:

Class 2, Constant Current, 100-277VAC, 50-60Hz, 2.5kV, 120V: 0.34A, 208V: 0.21A, 240V: 0.19A, 277V: 0.15A

Dimmable:

Driver includes dimming control for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims as low as 10%.

THD:

5.3% at 120V, 5.9% at 277V

Power Factor:

99.7% at 120V, 95.1% at 277V

LED Characteristics

Lifespan:

50,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

LEDs:

Long-life, high-efficiency, surface mount LEDs

Color Stability:

LED Color temperature is warrantied to shift no more than 200K in CCT over a 5 year period

Color Uniformity:

RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Construction

Cold Weather Starting:

The minimum starting temperature is -20°C (-4°F)

Maximum Ambient Temperature:

Suitable for use in 40°C (104°F) ambient temperatures

Housing:

Sheet metal stamping 24 gauge, cold-rolled steel

Reflector:

Sheet metal forming 24 gauge, cold-rolled steel with white powder coat

Lens:

Prismatic Acrylic Lens

Mounting:

Surface mount. Can be mounted with v-hooks (ordered separately).

Through Wire:

Fixtures can be daisy-chained with single AC input. Please refer to installation instructions for details.

Finish:

Formulated for high-durability and long lasting color

Green Technology:

Mercury and UV-free. RoHS compliant components.

Other

5 Yr Limited Warranty:

The RAB 5-year, limited warranty covers light output, color stability, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at

GUSJR4-40-835WU/LCTW

Features

- Affordable, easy to use LED wrap fixture
- 0-10V dimming standard
- 50,000-Hour LED lifespan

Ordering Matrix

Family	Length	Wattage	Color Temp	Finish	Voltage	Control Options	Options
GUSJR	4	40	835	W	U	/LC	TW
	2 = 2 ft	20 = 20W	850 = 5000K (Cool)	W = White	U = 120-277V, 0-10V Dimming	Blank = No Option	Blank = No Option
	4 = 4 ft	40 = 40W	840 = 4000K (Neutral)			/LC = Lightcloud Controller	/E2 = 120-277V Battery Backup
			835 = 3500K (Warm Neutral)				/TW = Through Wire