



Weight: 0.0 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

**Technical Specifications**

**Performance**

**Description:**

Microwave occupancy sensor kit

**Lightcloud**

**Lightcloud Blue Installed:**

Integrated/embedded networked lighting control, luminaire-level lighting control. Fixture, Zone, and plug-load control from one powerful device. LLLC - capable of switching, 0-10Vdimming, power/energy monitoring. Can also be used to extend the range of the Lightcloud Blue utilizes a "BLE Mesh" network communication protocols. Offers the capability to set the maximum light output to a less-than-maximum state of an individual luminaire at the time of installation or commissioning. The High-End trim functionality is field reconfigurable via the Lightcloud "BLE Mesh" network communication protocols. The Lightcloud Blue controller is designed to be attached to the fixture directly.  
 DLC system - N1XMLOEATBA  
[Learn more about Lightcloud.](#)

**Sensor Specifications**

**Sensor Sentivity:**

Low/Medium/High

**Occupancy Timeout:**

1min to 240mins

**Inside Occupancy Mode:**

Set vacant dim level from off and any dim level

**Daylight Threshold:**

150lux to 1500lux

**Sensor Warranty:**

5 year sensor warranty

**Mounting Height:**

Max 49ft(15m)

**Other**

**Compatible:**

H17 and H17 XL

**Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions

