
PS4-11-15WT





Square steel poles with welded tenon included for use with floodlights. Designed for ground mounting. Poles are stocked nationwide for quick shipment. Protective packaging ensures poles arrive at the job site good as new.

Color: Bronze

Weight: 134.0 lbs

Technical Specifications

istings	Height:
CSA Listed:	15 FT.
Suitable for wet locations.	Gauge:
Construction	11
Shaft:	Wall Thickness:
16,000 p.s.i. minimum yield.	1/8".
Hand Holes:	Shaft Size:
Reinforced with grounding lug and removable cover.	4".
Base Plates:	Hand Hole Dimensions:
Slotted base plates 36,000 p.s.i.	3" x 5".
Shipping Protection:	Bolt Circle:
All poles are shipped in individual corrugated cartons o prevent finish damage.	8 1/2".
	Base Dimension:
Color:	8".
Bronze powder coating.	
Tenon:	
Nelded 2 3/8" tenon included.	

Project:		Туре:	
Prepared By:		Date:	
Lamp Info		Ballast Info	
Туре:	N/A	Туре:	N/A
Watts:	0W	120V:	N/A
Shape/Size:	N/A	208V:	N/A
Base:	N/A	240V:	N/A
ANSI:	N/A	277V:	N/A
Hours:	N/A	Input Watts:	0W
Lamp Lumens:	N/A		
Efficacy:	N/A		

Weight:
134 lbs.
Anchor Bolt:
Galvanized anchor bolts and galvanized hardware and anchor bolt template. All bolts have a 3" hook.
Anchor Bolt Templates:
WARNING Template must be printed on 11" x 17" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available.
Pre-Shipped Anchor Bolts:
Bolts can be pre-shipped upon request for additional freight charge.
MaxEPA's/Max Weights:
70MPH 14.0 ft_/400 lb 80MPH 10.2 ft_/295 lb 90MPH 7.6 ft_/220 lb 100MPH 5.6 ft_/165 lb 110MPH 4.2 ft_/125 lb 120MPH 3.0 ft_/95 lb 130MPH 2.1 ft_/70 lb 140MPH 1.4 ft_/50 lb 150MPH 0.8 ft_/35 lb. Other
Terms of Sale:
Pole Terms of Sale is available .

PS4-11-15WT

2 3/8" —

Gauge - 11

4"

3/4

15'

Hand 18 hole 18

Dimensions



Features

Designed for ground mounting

Heavy duty TGIC polyester coating

Reinforced hand holes with grounding lug and removable cover for easy wiring access

Anchor Bolt Kit includes pole cap and base cover (sold separately)

Custom manufactured for each application

