

COILIGHT™ & COILIGHT™ REFLECTOR

COMPACT FLUORESCENT LAMPS

USHIO Coilights™ have an ultra compact shape that allows for maximum axial and radial light distribution and less trapping and light absorption. This allows for true incandescent A-lamp replacement and more efficient reflector lamps. Coilights are an energy efficient alternative to higher wattage incandescent lamps with up to 10 times more life.

USHIO Coilight™ & Coilight™ Reflector Series	Incandescent "A" Line Equivalent
13W.....	60W Incandescent
15W.....	65W Incandescent
18W.....	75W Incandescent
23W.....	75W Incandescent
26W.....	100W Incandescent


FEATURES & BENEFITS:

- Energy Efficient
- Long Life — Up to 10,000 Hours Average Life
- Low Mercury — Less than 2mg per Lamp
- 2700K & 4100K Color Temperatures
- Tri-phosphor Coating — High Color Rendering (80+ CRI)
- Integrated Electronic Ballast
- Same Light Profile as Incandescent Lamps
- Reflector Lamps for Area Lighting
- E26 & GU24 Base Types




COILIGHT™ & COILIGHT™ REFLECTOR


Compact Fluorescent Lamps for General Lighting




**E26
Coilight**



**GU24
Coilight**



**E26
PAR38**



**E26
R30**

Watts (W)	Ordering Code	Lamp Description	Dimensions			Color Temp (K)	CRI	Approx Lumens (lm)	Burn Position	Average Rated Life* (h)	Commercial Life** (h)	Case Qty
			Dia (in)	MOL (mm)	MOL (in)							
COILIGHT™ – E26 Base												
13	3000443	CF13CLT/2700/E26	1.8	104.14	4.1	2700	80+	825	Any	10000	12500	10
13	3000552	CF13CLT/4100/E26	1.8	104.14	4.1	4100	80+	800	Any	10000	12500	10
23	3000157	CF23CLT/2700/E26	2.1	124.46	4.9	2700	80+	1600	Any	10000	12500	10
23	3000555	CF23CLT/4100/E26	2.1	124.46	4.9	4100	80+	1600	Any	10000	12500	10
26	3000556	CF26CLT/4100/E26	2.1	129.54	5.1	4100	80+	1750	Any	10000	12500	10
COILIGHT™ – GU24 Base												
13	3000544	CF13CLT/2700/GU24	1.8	86.36	3.4	2700	80+	800	Any	10000	12500	10
13	3000545	CF13CLT/4100/GU24	1.8	86.36	3.4	4100	80+	800	Any	10000	12500	10
18	3000546	CF18CLT/2700/GU24	2.1	109.22	4.3	2700	80+	1200	Any	10000	12500	10
23	3000548	CF23CLT/2700/GU24	2.1	127.00	5.0	2700	80+	1600	Any	10000	12500	10
23	3000549	CF23CLT/4100/GU24	2.1	127.00	5.0	4100	80+	1600	Any	10000	12500	10
26	3000550	CF26CLT/2700/GU24	2.1	132.08	5.2	2700	80+	1610	Any	10000	12500	10
26	3000551	CF26CLT/4100/GU24	2.1	132.08	5.2	4100	80+	1725	Any	10000	12500	10
COILIGHT™ REFLECTOR R30 – E26 Base												
15	3000557	CF15R30/2700/E26	3.7	137.16	5.4	2700	80+	700	Any	10000	12500	12
COILIGHT™ REFLECTOR PAR38 – E26 Base												
23	3000559	CF23PAR38/2700/E26	4.8	127.00	5.0	2700	80+	1100	Any	10000	12500	12
23	3000560	CF23PAR38/4100/E26	4.8	127.00	5.0	4100	80+	1100	Any	10000	12500	12

* Based on ANSI / IESNA standards of 3 hours per start

** Based on estimated commercial operating standards of 12 hours per start

Reliable operating temperatures 0° F to 120° F

Coilights are not designed for dimming circuits or photocells

Coilights are not to be used in fully enclosed fixtures without adequate ventilation

- LAMP CONTAINS MERCURY

Manage in Accord with Disposal Laws

See: www.lamprecycle.org or 1-800-895-8842

Form No. S-CFL/0615

Specifications may be subject to change without prior notice. Refer to www.ushio.com for the most current product specifications.

USHIO