



GE
Lighting

20816 - GE MR16
Q20MR16/C/VNSP7
Product Photo



GENERAL CHARACTERISTICS

| | |
|--------------------------|------------------------|
| Base Description | 2-Pin |
| Base Type | Pin/Plug-In |
| Filament | CC-6 |
| Rated Life Hours-nominal | 3000 h |
| Lamp Enclosure Type | Enclosed fixtures only |
| Product Technology | Halogen |
| Base | GX5.3 |
| Bulb Shape | MR16 |

PHOTOMETRIC CHARACTERISTICS

| | |
|--------------------------------|---------|
| Beam Spread | 7 deg |
| Center Beam Candle Pwr Candela | 7400 cd |
| Color Temperature | 2900 K |

PRODUCT INFORMATION

| | |
|-----------------------------|-----------------|
| Product Code | 20816 |
| Description | Q20MR16/C/VNSP7 |
| Alternative Unit Of Measure | CASE |

DIMENSIONS

| | |
|----------|--------|
| Diameter | 2.0 in |
|----------|--------|

ELECTRICAL CHARACTERISTICS

| | |
|---------------------|------|
| Input Voltage [nom] | 12 V |
| Rated power (Watts) | 20 W |

CAUTIONS & WARNINGS

Warning

Risk of Burn

Allow lamp/fixture to cool before handling.

Turn power off before installing lamp.

Risk of Fire

Keep combustible materials away from lamp.

Use in enclosed fixture rated for this product-- see instructions.

Pressurized lamp--unexpected rupture may cause injury, fire, or property damage

Do not touch glass with bare hands.

Do not use lamp if outer glass is scratched or broken.

Use eye protection when handling lamp.

Use in enclosed fixture rated for this product.

Caution

Lamp may shatter and cause injury if broken

Dispose of lamp in a closed container.

Do not use lamp if outer glass is scratched or broken.