

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Energy efficient replacement for incandescent and halogen lamps
- Constructed from durable plastic which lowers risk of breakage
- Rated for use in enclosed and open fixtures in dry or damp locations
- Frosted lens produces smooth diffuse light
- Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs
- ENERGY STAR Compliant

Technical Specifications		
Performance	L70 Lifespan:	Beam Angle:
Product Type: A-Line 3 Way	15,000-Hour LED lifespan based on IES LM-70 results	200°
Input Wattage: 4.5W/9W/14.5W	Construction	Electrical
Lumens (Nominal): 500/900/1550	Bulb Shape: A19	Power Factor: >0.9
Color Accuracy: 80	Enclosure Material: Plastic	Input Voltage: 120V
Color Temperature: 2700K	Housing Finish: White	Operating Frequency: 60 Hz
Dimmable: Non-Dim	Lens Finish: Frosted	Operating Temperature: -20°C - 40°C
	Base Type: E26	

Technical Specifications (continued)

Other

Equivalency:

40W/60W/100W

Technology EQ:

Incandescent

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

Safety Listing:

UL Listed

Environment/Fixture Rating:

Damp / Open

ENERGY STAR V2.0:

This product is ENERGY STAR® Version 2.0 Certified

Energy Star ID:

2367402

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Model Number:

A10052(A19-4.5/9/14.5-E26-827-3WAY)

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
15.3 x 5.2 x 5.5	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	0	0	0
PALLET	1764	0	0	0

Dimension

