

<b>Project:</b>	<b>Type:</b>	<b>Prepared By:</b>	<b>Date:</b>
-----------------	--------------	---------------------	--------------



**Features and Benefits**

- Replaces CFL 18W, 26W, and 32W G24q Lamps
- Ballast Compatible. Directly Compatible with Most Existing CFL Ballasts.
- Compatible with G24q / GX24q (4-pin CFL) installations
- 50,000 hour Lifespan
- Environmentally friendly, no mercury used
- UL Listed, DLC Listed
- Rated for use in enclosed and open fixtures in dry or damp locations
- 5 Year No Compromise Warranty
- Compatible with RAB specified 0-10V dimming system

Technical Specifications		
<b>Performance</b>	<b>Compliance</b>	<b>Endcap Material:</b>
<b>Product Type:</b> A-Line	<b>UL Listed:</b> Suitable for damp locations	Aluminum
<b>Input Wattage:</b> 8.5W	<b>Enclosed Fixtures:</b> Suitable for use in enclosed fixtures	<b>Enclosure Material:</b> Plastic
<b>Typical Lumen Output:</b> 800lm	<b>DLC Model Number:</b> A10064(A19-8.5-E26-840-ND ECO)	<b>Beam Angle:</b> 200°
<b>Efficacy:</b> 94.1 lm/W	<b>LED Characteristics</b>	<b>Electrical</b>
<b>CRI:</b> 80	<b>Color Temperature:</b> 4000K	<b>Power Factor:</b> 0.7
<b>L70 Lifespan:</b> 15,000-Hour LED lifespan based on IES LM-70 results	<b>Construction</b>	<b>Operating Temperature:</b> -20°C - 45°C
	<b>Bulb Shape:</b> A19	
	<b>Base Type:</b> E26	

## Technical Specifications (continued)

### Electrical

**Input Voltage:**

120V

**Operating Frequency:**

60 Hz

### Other

**Warranty (Years):**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

**Wattage Equivalency:**

60W Incandescent

## Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	24	13.6	9.4	13.6
PALLET	2304	42.13	39.37	40.94

## Dimension

