A19-9-E26-930-F-F

Project: Type:	Prepared	By: Date:
UPC: 01925520073	F d P R L a T S	Features and Benefits Replacement for conventional decorative lamps Filament LED construction gives a unique traditional look and feel for decorative and ambient applications Produces rich and vibrant colors, >90CRI Rated for use in enclosed and open fixtures in dry and damp locations conger lifespan compared to legacy equivalents minimizes replacement and maintenance costs Title 20 Compliant, ENERGY STAR Compliant, UL Listed Semooth uniform dimming down to 10% (check dimmer compatibility list)
LISTED FCC CA20 COMPLIANT	WET ENERGY STAR	
	-Energy	
LISTED FCC CA20 COMPLIANT	-Energy	Endcap Material:
Image: Second system Image: Second system Technical Specifications Performance	WET RATED ENERGY STAR	Endcap Material: Aluminum
Performance	Dimmable:	
Product Type:	WET ENERGY STAR Dimmable: Yes, down to 10%	Aluminum Enclosure Material: Glass
Performance Product Type: Decorative nput Wattage:	Dimmable: Yes, down to 10% Compliance Enclosed Fixtures: Suitable for use in enclosed fixtures	Aluminum Enclosure Material: Glass Beam Angle:
Image: bit with the sector of the	Dimmable: Yes, down to 10% Compliance Enclosed Fixtures: Suitable for use in enclosed fixtures DLC Model Number:	Aluminum Enclosure Material: Glass Beam Angle: 360°
Performance Product Type: Decorative nput Wattage: WW Typical Lumen Output: B10lm	Dimmable: Yes, down to 10% Compliance Enclosed Fixtures: Suitable for use in enclosed fixtures DLC Model Number: F10019(A19-9-E26-930-F-F)	Aluminum Enclosure Material: Glass Beam Angle: 360° Electrical
Image: Sector of the sector of th	Dimmable: Yes, down to 10% Compliance Enclosed Fixtures: Suitable for use in enclosed fixtures DLC Model Number: F10019(A19-9-E26-930-F-F) LED Characteristics	Aluminum Enclosure Material: Glass Beam Angle: 360° Electrical Power Factor:
Performance Product Type: Decorative Input Wattage: WW Typical Lumen Output: B10Im Efficacy: 200 Im/W	Dimmable: Yes, down to 10% Compliance Biclosed Fixtures: Suitable for use in enclosed fixtures DLC Model Number: F10019(A19-9-E26-930-F-F) LED Characteristics Color Temperature:	Aluminum Enclosure Material: Glass Beam Angle: 360° Electrical Power Factor: >0.7
Image: bit is the bit	Dimmable:Yes, down to 10%ComplianceBuitable for use in enclosed fixturesSuitable for use in enclosed fixturesDLC Model Number:F10019(A19-9-E26-930-F-F)LED CharacteristicsColor Temperature:3000K	Aluminum Enclosure Material: Glass Beam Angle: 360° Electrical Power Factor: >0.7 Operating Temperature:
Image: bit is the bit	Dimmable: Yes, down to 10% Compliance Enclosed Fixtures: Suitable for use in enclosed fixtures DLC Model Number: F10019(A19-9-E26-930-F-F) LED Characteristics Color Temperature: 3000K Construction	Aluminum Enclosure Material: Glass Beam Angle: 360° Electrical Power Factor: >0.7
Image: bit is the bit	Dimmable: Yes, down to 10% Compliance Enclosed Fixtures: Suitable for use in enclosed fixtures DLC Model Number: F10019(A19-9-E26-930-F-F) LED Characteristics Color Temperature: 3000K Construction Bulb Shape:	Aluminum Enclosure Material: Glass Beam Angle: 360° Electrical Power Factor: >0.7 Operating Temperature:
Image: bit is the bit	Dimmable: Yes, down to 10% Compliance Enclosed Fixtures: Suitable for use in enclosed fixtures DLC Model Number: F10019(A19-9-E26-930-F-F) LED Characteristics Color Temperature: 3000K Construction	Aluminum Enclosure Material: Glass Beam Angle: 360° Electrical Power Factor: >0.7 Operating Temperature:

E26

Electrical	Electrical Characteristics	Wattage Equivalency:
Input Voltage:	Flicker:	60W Incandescent
20V	<30%	
Operating Frequency:	Other	
60 Hz	Warranty (Years):	
	RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty.</u>	

Case and Pallet Dimensions							
	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)			
CASE	12	10.8	8.1	10.8			
PALLET	1080	44.09	38.74	26.67			

