



UPC: 192552014489

Weight: 0.0 lbs

| | |
|--------------|-------|
| Project: | Type: |
| Prepared By: | Date: |

Technical Specifications

| | | |
|--|---|--|
| <p>Performance</p> <p>Product Type: A-Line</p> <p>Input Wattage: 23W</p> <p>Lumens (Nominal): 2550lm</p> <p>Efficacy: 110.9 lm/W</p> <p>Color Accuracy (CRI): >80 CRI</p> | <p>L70 Lifespan: 25,000-Hour LED lifespan based on IES LM-70 results</p> <p>Dimmable: Yes</p> <p>Compliance</p> <p>UL Listed: Suitable for damp locations</p> <p>Enclosed Fixtures: Suitable for use in enclosed fixtures</p> <p>LED Characteristics</p> <p>Color Temperature: 2700K</p> | <p>Construction</p> <p>Bulb Shape: A21</p> <p>Base Type: E26</p> <p>Enclosure Material: Plastic</p> <p>Optical</p> <p>Beam Angle: 230°</p> |
|--|---|--|

Technical Specifications (continued)

Electrical

Power Factor:

>0.9

Operating Temperature:

-20°C - 40°C

Input Voltage:

120V

Operating Frequency:

60 Hz

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Wattage Equivalency:

150W Incandescent / Metal Halide or High Pressure Sodium

Case and Pallet Dimensions

| | QTY | LENGTH (in) | WIDTH (in) | HEIGHT (in) |
|--------|-----|-------------|------------|-------------|
| CASE | 12 | 12.8 | 9.6 | 5.9 |
| PALLET | 0 | 0 | 0 | 0 |

Features

Replacement for High-output Incandescent or lower wattage metal halide and high pressure sodium lamps

Rated for use in enclosed and open fixtures in dry or damp locations

Ideal for post top, bollards, and outdoor corridor lighting

Suitable for use in a base-up or base-down position

Ordering Matrix

| Family | Wattage | Base Type | CRI/Color Temp | Dimmable |
|--------|--|------------------------------------|---|---------------------------------------|
| A21 | 23 | E26 | 827 | DIM |
| | 5 = 5W 9 = 9W 10 = 10W 13 = 13W 15 = 15W 16 = 16W 23 = 23W | E26 = E26 Base GU24 = GU24 Base | 850 = 80 CRI, 5000K 840 = 80 CRI, 4000K 835 = 80 CRI, 3500K 830 = 80 CRI, 3000K 827 = 80 CRI, 2700K | DIM = Dimmable DIM 120V = Dimmable |