



16" or 22" High Bay Aluminum: Indoor fixtures for use above 25'. 16" units for 250w Metal Halide. 22" units for 400w Metal Halide. Die cast aluminum housing and wiring box and semi-specular anodized aluminum refractor. Ballast and lamp supplied.

Color: N/A

Weight: 22.4 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Lamp Info		Ballast Info	
Type:	ED28	Type:	CWA-HPF QT
Watts:	250W	Watts:	1.4/2.5A
Shape/Size:	N/A	208V:	.8/1.5A
Base:	N/A	240V:	.7/1.3A
ANSI:	N/A	277V:	.6/1.1A
Hours:	15,000	Input Watts:	278W
Lamp Lumens:	23,800	Efficiency:	90%
Efficacy:	86 LPW		

## Technical Specifications

### Listings

#### UL Listing:

UL Listed for 65° C (149° F) ambient temperature. Damp locations.

#### UL Listing:

Suitable for damp locations. UL and cUL listed for 40°C (104°F) ambient temperature.

### Construction

#### Housing:

Heavy die cast aluminum housing with powder coat finish.

#### Junction Box:

Heavy duty stamped steel junction box.

#### Housing:

Die cast aluminum housing with an open air ballast for cooler operation.

#### Plate:

Die-cast plate tapped 3/4" NPS accepts 3/4" pipe or 715NEW die cast hook.

#### Reflector:

Reflector with five distribution patterns for precise control.

#### Housing:

Die cast aluminum painted white. 3' cord and safety hook. Heavy-duty sheet metal wiring box with 1/2 knockouts and easy leveling adjustment.

#### Reflector:

Seven distribution patterns for precise control with seven position adjustable bracket. Spun semi-specular anodized aluminum.

### Electrical

#### Socket:

Mogul base open rated socket.

#### Ballast:

Quad Tap. All fixtures are wired for 277V at the factory.

#### Ballast:

Multi-Tap Ballast (120/208/240/277 Volts).

#### Ballast:

High power factor ballast with class H insulation.

#### Socket:

4Kv pulse rated mogul-base porcelain socket, spring loaded center contact.

#### Wiring Compartment:

Removable steel wiring compartment door for quick and easy mounting.

#### Start Up Time:

3 - 5 minutes.

#### Restrike Time:

10 - 20 minutes.

#### Pulse Start:

Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency.

### Ballast:

Quad-Tap CWA Ballast (120/208/240/277 Volt).

### Socket:

4KV Pulse rated Mogul Base socket for open rated lamps.

### 2005 NEC Compliance:

Open rated lamp and socket comply with 2005 NEC code .

### Optical

#### Patterns:

Field adjustable light distribution patterns.

#### Lamp:

Mogul Base Up, open rated BT37 supplied.

### Other

#### Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

#### Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

#### Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

## Technical Specifications (continued)

### Other


#### Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

#### GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

## Dimensions



## Features

- CSA Certified for Indoor Locations
- Supplied with safety hook and 3 foot cord
- Use indoors above 25'
- Ballast and lamp included