



Metal Halide HID with temporary guard.

Color: N/A

Weight: 21.1 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Lamp Info		Ballast Info	
Type:	BT28	Type:	CWA HPF QT
Watts:	250W	120V:	1.4/2.5A
Shape/Size:	N/A	208V:	.8/1.5A
Base:	N/A	240V:	.7/1.3A
ANSI:	N/A	277V:	.6/1.1A
Hours:	15,000	Input Watts:	278W
Lamp Lumens:	23,800	Efficiency:	90%
Efficacy:	86 LPW		

## Technical Specifications

### Listings

#### UL Listing:

Suitable for damp locations

### Construction

#### Housing:

Die cast aluminum housing and wiring box with 1/2" NPS knockouts and easy leveling adjustment. Comes with 3' cord, hook/loop and safety chain.

#### Mounting Box:

Die-cast aluminum mounting box tapped for 3/4" conduit.

### Electrical

#### Ballast:

Quad-Tap CWA Ballast (120/208/240/277 Volt).

#### Watts:

250 Watt.

#### 2005 NEC Compliance:

Open rated lamp and socket comply with 2005 NEC code .

### Optical

#### Lamp:

Mogul Base Up BT28 Metal Halide lamp supplied.

## Features

Rugged hook/loop with 3' cord or easy installation

Heavy duty die cast housing

Pulse rated Mogul Base Socket for open rated lamps