## CF-FF120-G-W





Project:	Туре:
Prepared By:	Date:

Color: Green

## **Technical Specifications**

Construction	LED Characteristics	Buy American Act Compliance:	
Lens:	Light Loss Factor:	RAB values USA manufacturing! Upon request, RAB	
Tempered, soda lime glass, 3mm thick (nominal 1/8");	0.07	may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.	
can be sand blasted for additional diffusion	Other		
Color:	Color Filter:		
Fade-resistant color is molded into the glass	Green		
Frame and L Rails:	Compatibility:		
Die-formed 0.40 aluminum with powder-coated finish	FFLED 120W in white finish		

## Features

Simple to install or swap colors (4 screws for easy mounting)

Durable, tempered glass withstands outdoor use

Aluminum frame construction with RAB's durable, polyester power-coat finish

## **Ordering Matrix**

Family	Fixture	Filter Color	Frame Finish
CF	FF120	G	W
	FX300 = FXLED300 FXLED200 FX150 = FXLED150 FXLED125 FXLED105 FXLED78 EZ78 = EZLED78 CANVAS78 FF120 = FFLED120 FF80 = FFLED20 FFLED22 FFLED39 FFLED26	B = Blue $LB = Light Blue$ $G = Green$ $MG = Medium Green$ $LG = Light Green$ $R = Ruby Red$ $MR = Cherry Red$ $MA = Medium Amber$ $LA = Light Amber$ $PP = Pale Purple$ $Y = Yellow$	A = Bronze W = White
	<b>FF18</b> = FFLED18		

Need help? Tech help line: (888) RAB-1000 Email: sales@rabweb.com Website: www.rabweb.com

Copyright © 2014 RAB Lighting Inc. All Rights Reserved Note: Specifications are subject to change at any time without notice