

Project: _____ Type: _____ Prepared By: _____ Date: _____



Features and Benefits

- Energy efficient replacement for incandescent and halogen Small diameter reflectors
- Constructed from durable materials which lowers risk of breakage
- Rated for use in enclosed and open fixtures in dry or damp locations
- Single optic and full face lens for precise beam angle control
- Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs
- ENERGY STAR Compliant, UL Listed
- Compatible with low voltage transformers (check compatibility list)

Technical Specifications

Performance		Dimmable:	Beam Angle:
Product Type:	Small-Reflector	Yes, down to 10%	35°
Input Wattage:	4.5W	L70 Lifespan:	Electrical
Lumens (Nominal):	350	25,000-Hour LED lifespan based on IES LM-70 results	Power Factor:
Efficacy:	77 lm/W	Construction	>0.7
Color Accuracy:	80	Bulb Shape:	Input Voltage:
Color Temperature:	4000K	PAR16	120V
		Enclosure Material:	Operating Frequency:
		Plastic	60 Hz
		Housing Finish:	Operating Temperature:
		White	-20°C-45°C
		Base Type:	
		GU10	

Technical Specifications (continued)

Other

Equivalency:

50

Technology EQ:

Halogen

Warranty (Years):

3 years

Compliance

UL Listed:

Yes

Environment/Fixture Rating:

Damp / Enclosed

Rohs:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Model Number:

R10061(GU10-4.5-840-35D-DIM)

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
10.43 x 4.33 x 2.76	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	10	0	0	0
PALLET	3120	0	0	0

Dimension

