HID-135-V-EX39-850-BYP-HB



Replace up to 600W MH lamps for High Bays. Ultra slim and lightweight design, 90 degree beam angle. Replace the old luminaire with this sleek design for a whole new look and feel.

Color: White

Weight: 3.6 lbs

Project: Type: Prepared By: Date: LED Info **Driver Info** Input Voltage 120-277 Watts 135.00W 5000K (Daylight) Power Factor 0.9 Color Temp Lumens 20,000 Flicker N/A THDi Efficacy 148.1 LPW N/A Color Accuracy 80 CRI R9

L70 Accuracy 50,000

Technical Specifications

Technical Specifications	CRI:	Installation Type:
Product Type:	80	Type B, Ballast Bypass
HID	Base Type:	Installation Orientation:
Bulb Shape:	EX39	Vertical
High Bay	L70 Lifespan:	For Use in Emergency Fixtures:
Wattage:	50,000 hours	No
135W	Operating Temperature:	For Use Outdoors in Open Fixtures:
Wattage Equivalency:	-20°C - 45°C	No
400W/600W HID	Dimmable:	Electrical Characteristics
Typical Lumen Output:	No	Input Voltage:
20000	Beam Angle:	120-277V
Efficacy:	90°	
148 lm/W	Warranty:	
Color Temperature:	5-Year, No-Compromise Warranty	
5000K Daylight		

Technical Specifications (continued)			
Electrical Characteristics	Input Current @ 277V:	CEC Status:	
Power Factor:	598mA	Lawful for sale in California	
0.9	Listings		
Operating Frequency:	UL Recognized:		
50 / 60 Hz	Yes		
Input Current @ 120V:	UL Classified:		
1109mA	Yes		