HID-30-H-EX39-850-BYP-WP



Replace 100W up to 250W MH lamps for Wall Packs. Water/dust resistant. Uses 76% less energy than MH. 350° rotatable base puts light where you need it.

Color: White Weight: 1.6 lbs

Project:	Туре:
Prepared By:	Date:

Driver Info LED Info

 Watts
 30.00W
 Input Voltage 100-277V

 Color Temp
 5000K (Daylight)
 Power Factor >0.9

 Lumens
 4,650
 Flicker
 <30%</td>

 Efficacy
 155 LPW
 THDi
 N/A

Color Accuracy 80 CRI R9

L70 Accuracy 50,000

Technical Specifications

Technical Specifications

Product Type:

HID

Bulb Shape:

Wall Pack

Wattage:

30W

Wattage Equivalency:

150W HID

Typical Lumen Output:

4650

Efficacy:

155 lm/W

Color Temperature: 5000K Daylight

CRI:

80

Base Type:

EX39

L70 Lifespan:

_, c _,,cop.

50,000 hours

Operating Temperature:

-30°C - 60°C

Dimmable:

No

Beam Angle:

180°

Warranty:

5-Year, No-Compromise Warranty

Installation Type:

Type B, Ballast Bypass

Installation Orientation:

Universal Installation

For Use in Emergency Fixtures:

No

For Use Outdoors in Open Fixtures:

No

Electrical Characteristics

Input Voltage:

100-277V

HID-30-H-EX39-850-BYP-WP



Technical Specifications (continued)

Electrical Characteristics UL Classified: Flicker:

<30% Yes **Power Factor:** THDi: **CEC Status:**

<20% Lawful for sale in California **Operating Frequency:**

Listings 50 / 60 Hz **UL Listed:**

0.3mA Yes

Input Current @ 120V:

Dimensions 4 5/8 " 117.1mr

Features

HID REPLACEMENT - Replace conventional HID lamps

BALLAST BYPASS - Internal driver eliminates the need for external driver or ballast

COMPACT DESIGN - Allows the lamp to fit in most fixtures

INSTALLATION ORIENTATION - Lamps can be installed universally Base up, down or sideways

HEAT DISSIPATION - Thermal technology extends lifespan

WATER & DUST RESISTANT - Ideal for outdoor fixtures

ENCLOSED FIXTURE RATED - May be used in enclosed and open fixtures

ENERGY SAVINGS - Uses 76% less energy than traditional lamps

MERCURY FREE - Environmentally friendly vs fluorescent technologies

350° ROTATABLE BASE - Direct light where needed