on IES LM-70 results

HID-80-H-EX39-850-BYP-SB



Replace 250 - 400W HID lamps for shoebox area lights. Water/dust resistant. LED uses approximately 76% less energy than traditional HID lamps. Expandable flaps and rotatable base.


Color: White

Weight: 2.4 lbs

Project: Type: Prepared By: Date: **Driver Info** LED Info Watts: 80W Input Voltage: 100-277V 5000K (Daylight) Power Factor: Color Temp: 0.9 Flicker: Lumens: 10,000 <30% 125 LPW THDi: <20% Efficacy: Color Accuracy: 80 CRI L70 Accuracy: 50,000

Technical Specifications		
Listings	Bulb Type:	LED Characteristics
UL Listed:	Shoe Box	Lifespan:
Yes	Base Type:	50,000-hour LED lifespan based of
UL Classified:	EX39, Mogul Base	Other
Yes	Dimmable:	Equivalent:
FCC:	No	320W/250W HID Shoe Box
Yes	Construction	Warranty:
Rohs:	Operating Temperature:	5 years
Yes	-20 - 40°C	Optical
CEC Status:	Bare Lamp Illuminated Length (inches):	Beam Angle:
Lawful for sale in California	4.80"	180°
DLC Qualified:	MOL (inches):	Shipping Information
Yes	8.74"	Case Qty:
DLC Listed:	MOD (inches):	6
This product is on the Design Lights Consortium (DLC)	4.92"	Case Dimensions:
Qualified Products List and is eligible for rebates from DLC Member Utilities.	Minimum Compartment Size (inches):	17.52 x 10.91 x 13.58
DLC Product Code: P9STN6S7	Length: 11.02"	Pallet Quantity of Pieces:
Description	Width: 11.02" Height: 12.24"	108
Lamp Type:		Pallet Dimensions:
HID		34.69 x 37.01 x 45.47

HID-80-H-EX39-850-BYP-SB



Features

Uses 76% less energy than traditional lamps

Integral Driver, Eliminates the Need for External Driver or Ballast

Includes 4kV Surge Protection

- 350 $^{\circ}$ rotatable base, directs light where needed
- Integrated Heat Sink Quickly Dissipates Heat
- Suitable for Use in Fully Enclosed Fixture
- Water and dust resistant, ideal for outdoor use

Environmentally friendly: No Mercury Used