



Small size ideal for junction box mounting in wireless or other modern lighting control systems. Integral test switch and LED allows for quick testing and verification of proper functionality.

Color: White

Weight: 0.8 lbs

Project:	Type:
Prepared By:	Date:

Technical Specifications

Listings

UL Listing:

UL924 Listed

Electrical

Sensing Input:

120V - 277V

Load Rating:

120V - 277V (20A)

Ballast Load Rating:

20A (120V - 277V)

Incandescent Load:

1800W (120V) / 1500W (277V)

Load:

Contact #1 20A (120V-277V)

Mechanical

Mounting:

Universal (flush, panel, fixture or junction box mount)

Rating:

UL94V-0A

Shipping Weight:

12 oz

Temperature:

32°F - 140°F (0°C - 60°C)

Size:

1.7" x 3" x 1.2" (W x H x D body)

Other

Warranty:

10-year full hardware warranty with 100% repair/replacement coverage for all properly installed devices.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Features

LED compatible

20A Rated N/O & N/C

Used for bypassing line voltage switching, occupancy sensors or dimmers

Also used as dry contact to signal relay panels or BMS systems of utility power interruption

Integral test switch and green utility power indicator

UL924 Listed