PAR30L-19-E26-940-40D-ND

Project:	Туре:	Prepared By: Date:	
		Features and Benefits	
	in the second se	Replacement for High output incandescent/halogen or cer metal halide HID Lamps	ramic
		Commercial Grade	
		Large metal heatsink for optimal heat dissipation	
		In HID retrofit applications - Integral Driver enables lamp wired directly to line voltage. Must bypass ballast.	to be
		Produces rich and vibrant colors >90CRI	
		Energy efficient replacement for incandescent and haloge lamps	en PAR
		Constructed from durable materials which lowers risk of b	oreakage
		Rated for use in enclosed and open fixtures in dry and da locations	mp
	Y	Single optic and full face lens for precise beam angle con	trol
	UPC: 01.93E+11	Longer lifespan compared to legacy equivalents minimize replacement and maintenance costs	S
		Title 20 Compliant, Energy Star Compliant, UL Listed	
LISTED		Energy STAR	

Technical Specifications

Performance	L70 Lifespan:	Optical	
Product Type:	50,000-Hour LED lifespan based on IES LM-70	MBCP: 3400 Electrical Power Factor:	
Commercial PAR	results		
Input Wattage:	Construction		
19W	Bulb Shape:		
Lumens (Nominal):	PAR30L	>0.9	
1800	Enclosure Material:	Input Voltage:	
Color Accuracy:	Die Cast Aluminum	120-277V	
90 CRI	Housing Finish:	Operating Frequency:	
Color Temperature:	White	60 Hz	
4000K	Base Type:	Operating Temperature:	
Dimmable:	E26	-20°C - 45°C	
Non-Dim	Beam Angle:	-20 C - 45 C	
	40°		

RAB

Technical Specifications (continued)

Other

Equivalency:

75W Halogen / 39W CMH

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Environment/Fixture Rating:

Damp / Open

ENERGY STAR V2.0: This product is ENERGY STAR® Version 2.0 Certified

Energy Star ID:

2366168

T20 Compliant:

Yes, Title 20 Tier 2

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Model Number:

P10029(PAR30L-19-E26-940-40D-ND)

Compliance

Safety Listing:

UL Listed

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity	
7.8 x 5.1 x 11.8	1	

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	1	0	0	0
PALLET	720	0	0	0

Dimension

