PLC-9-V-827-DIR

Color Temperature:

2700K Soft White

Project:	Туре:	Prepared By:	Date:
Image: Constraint of the second se	<image/> <section-header><section-header></section-header></section-header>	INSTANT ON HIGH EFFIC/ less energy 50,000-HOU lamps MERCURY F technologie	FIXTURE RATED - May be used in both enclosed and
Technical Specification			
Technical Specifications	CRI:		Electrical Characteristics
Product Type:	Base Type:		Operating Frequency:
Compact			Pallact Dependent
			Ballast Dependent
-	G24q		Input Voltage:
PLC	G24q L70 Lifespan:		Input Voltage: Ballast Dependent
PLC Finish:	G24q L70 Lifespan: 50,000 hours		Input Voltage: Ballast Dependent Power Factor:
PLC Finish: Frosted	G24q L70 Lifespan: 50,000 hours Warranty:	arrantu	Input Voltage: Ballast Dependent Power Factor: Ballast Dependent
PLC Finish: Frosted Wattage:	G24q L70 Lifespan: 50,000 hours Warranty: 6-Year, No-Compromise Wa	arranty	Input Voltage: Ballast Dependent Power Factor: Ballast Dependent THDi:
PLC Finish: Frosted Wattage:	G24q L70 Lifespan: 50,000 hours Warranty: 6-Year, No-Compromise Wa Installation Type:	arranty	Input Voltage: Ballast Dependent Power Factor: Ballast Dependent THDi: <20%
Bulb Shape: PLC Finish: Frosted Wattage: 9W Efficacy: 100 lm/W	G24q L70 Lifespan: 50,000 hours Warranty: 6-Year, No-Compromise Wa		Input Voltage: Ballast Dependent Power Factor: Ballast Dependent THDi:

Suitable for damp locations. Suitable for use in enclosed fixtures.

No

RAB

Technical Specifications (continued)

LENGTH (in)

Listings

CASE

PALLET

CEC Status:

Application:

HEIGHT (in)

5.1

0

WIDTH (in)

6.1

0

Other

:

Lawful for sale in California

Case and Pallet Dimensions

8.1

0

ΟΤΥ

12

2880

Suitable for damp locations and totally enclosed fixtures.

Wiring Diagram



