RAB Lamps



Project: Prepared By:		Туре:	
		Date:	
Driver Info		LED Info	
Watts:	17W	Input Voltage:	120-277V
Color Temp:	5000K (Daylight)	Power Factor:	0.9
Lumens:	2,200	Flicker:	N/A
Efficacy:	129 LPW	THDi:	<20%
Emocoy.			
Color Accuracy:	82 CRI		

Technical Specifications		
Listings	Description	MOD (inches):
UL Recognized:	Lamp Type:	0.06"
Yes	PLL Compacts	Other
UL Classified:	Bulb Type:	Equivalent:
Yes	PLL	40W Fluorescent PLL
NSF:	Base Type:	Warranty:
Complies with NSF	2G11, 4 Pin	5 years
FCC:	Dimmable:	Shipping Information
Yes	No	Case Qty:
Rohs:	Material:	25
Yes	Glass	Case Dimensions:
CEC Status:	LED Characteristics	23.62 x 9.76 x 6.5
Lawful for sale in California	Installation Type:	Pallet Quantity of Pieces:
DLC Qualified:	Туре В	1200
Yes	Lifespan:	Pallet Dimensions:
DLC Listed:	50,000-hour LED lifespan based on IES LM-70 results	47.24 x 39.37 x 40.16
This product is on the Design Lights Consortium (DLC)	Construction	
Qualified Products List and is eligible for rebates from DLC Member Utilities.	Operating Temperature:	
DLC Product Code: PQWNE0TM	-20 - 40°C	

Need help? Tech help line: (888) RAB-1000 Email: sales@rablighting.com Website: www.rablighting.com Copyright © 2018 RAB Lighting Inc. All Rights Reserved Note: Specifications are subject to change at any time without notice

PLL-17-850-BYP

A: 22 1/16" 560mm

B: 22 5/16" 567mm D: 11/16" 17.45mm

(:

C: 1 1/2" 38.45mn

Dimensions

Features

Replacement for Conventional Fluorescent Lamps

Approximately 40% More Energy Efficient that Conventional Pin-Base CLF's with 2G11 base

Instant on, no flicker or hum

Internal Driver, Eliminates the need for External Driver or Ballast

111+ Lumens per watt

Environmentally friendly: No Mercury Used