



Replace existing twin tube PL lamps with a GX23 base. Can be installed on the existing ballast or wired directly to line voltage

Color: White

Weight: 0.2 lbs

Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Watts	5.00W	Input Voltage	N/A
Color Temp	3000K (Warm White)	Power Factor	>0.9
Lumens	500	Flicker	≤30%
Efficacy	100 LPW	THDi	N/A
Color Accuracy	82 CRI	R9	
L70 Accuracy	50,000		

Technical Specifications

Technical Specifications

Product Type:

Compact

Bulb Shape:

PLS

Finish:

Frosted

Wattage:

5W

Wattage Equivalency:

13W Fluorescent

Typical Lumen Output:

500

Efficacy:

90 lm/W

Color Temperature:

3000K Warm White

CRI:

82

Base Type:

Gx23

L70 Lifespan:

50,000 hours

Operating Temperature:

-20°C - 45°C

Dimmable:

No

Beam Angle:

150°

Warranty:

5-Year, No-Compromise Warranty

Installation Type:

Hybrid, Works with or without Ballast

Installation Orientation:

Horizontal

For Use in Emergency Fixtures:

No

For Use Outdoors in Open Fixtures:

No

Technical Specifications (continued)

Electrical Characteristics

Power Factor:

>0.9

Operating Frequency:

Ballast Dependent or 50/60 Hz

Input Current @ 120V:

52mA

Input Current @ 277V:

24mA

Flicker:

≤30%

Listings

UL Listed:

Yes

UL Classified:

Yes

CEC Status:

Lawful for sale in California