



Replace existing twin tube PL lamps with a GX23 base. Can be installed on the existing ballast or wired directly to line voltage

Color: White

Weight: 0.2 lbs

Project:

Type:

Prepared By:

Date:

Driver Info

Watts 5.00W
 Color Temp 4000K (Cool White)
 Lumens 500
 Efficacy 100 LPW
 Color Accuracy 82 CRI
 L70 Accuracy 50,000

LED Info

Input Voltage N/A
 Power Factor >0.9
 Flicker ≤30%
 THDi N/A
 R9

Technical Specifications

Technical Specifications

Product Type:

Compact

Bulb Shape:

PLS

Finish:

Frosted

Wattage:

5W

Wattage Equivalency:

13W Fluorescent

Typical Lumen Output:

500

Efficacy:

100 lm/W

Color Temperature:

4000K Cool White

CRI:

82

Base Type:

Gx23

L70 Lifespan:

50,000 hours

Operating Temperature:

-20°C - 45°C

Dimmable:

No

Beam Angle:

150°

Warranty:

5-Year, No-Compromise Warranty

Installation Type:

Hybrid, Works with or without Ballast

Installation Orientation:

Horizontal

For Use in Emergency Fixtures:

No

For Use Outdoors in Open Fixtures:

No

Technical Specifications (continued)

Electrical Characteristics

Power Factor:

>0.9

Operating Frequency:

Ballast Dependent or 50/60 Hz

Input Current @ 120V:

52mA

Input Current @ 277V:

24mA

Flicker:

≤30%

Listings

UL Listed:

Yes

UL Classified:

Yes

CEC Status:

Lawful for sale in California