



Project:	Туре:
Prepared By:	Date:

# **Technical Specifications**

## Listings

#### **CSA Listed:**

Suitable for wet locations

# Construction

#### **Description:**

Steel pole 5" round 7 gauge 30 foot welded tenon square base

## **Shaft:**

46,000 p.s.i. minimum yield.

#### **Hand Holes:**

Reinforced with grounding lug and removable cover

### **Base Plates:**

36,000 p.s.i. minimum yield.

### **Color:**

Bronze powder coating

### Height:

30 FT

#### Gauge:

7

#### Wall Thickness:

3/16"

## **Shaft Size:**

5"

### **Anchor Bolt Templates:**

WARNING Template must be printed on 12" x 18" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available <u>online</u>.

#### Max EPA's/Max Weights:

70MPH 11.8 ft./380 lb. 80MPH 7.6 ft./360 lb. 90MPH 4.7 ft./310 lb. 100MPH 2.6 ft./290 lb. 110MPH 1.1 ft./270 lb

## **Accessories:**

Base/Cap: <u>BASE-R5</u> Anchor Bolts: <u>BOLT5-8</u>

#### Other

## **Terms of Sale:**

Pole Terms of Sale is available online.



# **Technical Specifications (continued)**

#### Other

### **Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

### **Dimensions**



#### **Features**

Designed for ground mounting

Heavy duty TGIC polyester coating

Reinforced hand holes with grounding lug and removable cover for easy wiring access

Pole caps, base covers & bolts are sold separately

Custom manufactured for each application

# **Ordering Matrix**

Family	Shape	Size	Gauge	Height	Drilled/Welded Tenon
Р	R	5	7	30	WT
	R = Round TR = Taped Round	4 = 4" 5 = 5" 6 = 6" 7 = 7" 8 = 8"	<b>7</b> = 7 <b>11</b> = 11	10 = 10' 15 = 15' 20 = 20' 25 = 25' 30 = 30'	D2 = Drilled WT = Welded Tenon