PS25-32-E26-840-ND 120-277V



Replace 300W A19 lamps. These universal voltage bulbs work on 120 or 277V for maximum flexibility across applications.

Color: White Weight: 1.0 lbs

Project:	Туре:
Prepared By:	Date:

Driver Info

31.50W

4000K (Cool White)

Lumens 4,100

Watts

Color Temp

Efficacy 130.2 LPW Color Accuracy 80 CRI

L70 Accuracy 40,000

LED Info

Input Voltage 120-277 Power Factor >0.9

Flicker N/A THDi N/A

R9

Technical Specifications

Technical Specifications

Product Type:

A-Line

Bulb Shape:

PS25 E26

Wattage:

0.4 514/

31.5W

Wattage Equivalency:

300WW Incandescent

Typical Lumen Output:

4100

Efficacy:

128 lm/W

Color Temperature: 4000K Cool White

CRI:

80

Base Type:

E26

L70 Lifespan:

40,000 hours

Operating Temperature:

-20°C - 45°C

Dimmable:

No

INO

Beam Angle:

230°

Warranty:

5-Year, No-Compromise Warranty

For Use in Emergency Fixtures:

No

For Use Outdoors in Open Fixtures:

No

Electrical Characteristics

Input Voltage: 120-277V

Power Factor:

>0.9

Operating Frequency:

60 Hz

PS25-32-E26-840-ND 120-277V



Technical Specifications (continued)

Electrical Characteristics THDi: UL Classified:


Input Current @ 120V: ≤25%

330mA Listings CEC Status:

Input Current @ 277V: UL Listed: Not lawful for sale in California

143mA Yes

Dimensions



Features

UNIVERSAL BULBS: Replace 60W, 125W, 200W and 300W incandescent lamps operated on 120V or 277V

UNIVERSAL voltage bulbs have high lumen packages for industrial and commercial applications

ENERGY SAVINGS: Save up to 85% on energy

Yes

ENCLOSED FIXTURE RATED: May be used in both enclosed and open fixtures

DAMP RATED: Suitable for damp locations

SHATTERPROOF: Plastic constructed bulbs ideal for rugged applications