
## PS5-07-25D2





Square steel poles drilled for 2 Area Lights at 180°. Designed for ground mounting. Poles are stocked nationwide for quick shipment. Protective packaging ensures poles arrive at the job site good as new.

Color: Bronze

Weight: 319.0 lbs

## **Technical Specifications**

Project:		Туре:	
Prepared By:		Date:	
Lamp Info		Ballast Info	
Туре:	N/A	Type:	N/A
Watts:	0W	120V:	N/A
Shape/Size:	N/A	208V:	N/A
Base:	N/A	240V:	N/A
ANSI:	N/A	277V:	N/A
Hours:	N/A	Input Watts:	0W0
Lamp Lumens:	N/A		

N/A

Listings	Gauge:	Anchor Bolt:	
CSA Listed:	7	Galvanized anchor bolts and galvanized hardware and	
Suitable for wet locations.	Wall Thickness:	anchor bolt template. All bolts have a 3" hook.	
Construction	3/16"	Anchor Bolt Templates:	
Shaft:	Shaft Size:	WARNING Template must be printed on 11" x 17" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available.	
46,000 p.s.i. minimum yield.	5"		
Hand Holes:	Hand Hole Dimensions:		
Reinforced with grounding lug and removable cover.	3" x 5"	Pre-Shipped Anchor Bolts:	
Base Plates:	Bolt Circle:	Bolts can be pre-shipped upon request for additional freight charge.	
36,000 p.s.i. minimum yield.	11"	MaxEPA's/Max Weights: 70MPH 19.6 ft_/450 lb 80MPH 13.9 ft_/320 lb 90MPH 9.8 ft_/225 lb 100MPH 6.7 ft_/155 lb 110MPH 4.4 ft_/100 lb	
Shipping Protection:	Base Dimension:		
All poles are shipped in individual corrugated cartons	11"		
to prevent finish damage.	Weight:		
Color:	319 lbs.		
Bronze powder coating.		120MPH 2.6 ft_/60 lb	
Height:		130MPH 1.2 ft_/25 lb.	
25 FT.		Other	
		Terms of Sale:	
		Pole Terms of Sale is available .	

Efficacy:

## Features

Designed for ground mounting

Heavy duty TGIC polyester coating

Reinforced hand holes with grounding lug and removable cover for easy wiring access

Anchor Bolt Kit includes pole cap and base cover (sold separately)

Custom manufactured for each application