
PS5-07-30D2





Square steel poles drilled for 2 Area Lights at 180°. Designed for ground mounting. Poles are stocked nationwide for quick shipment. Protective packaging ensures poles arrive at the job site good as new.

Color: Bronze

Weight: 433.0 lbs

Technical Specifications

Project:		Туре:	
Prepared By:		Date:	
Lamp Info		Ballast Info	
Туре:	N/A	Туре:	N/A
Watts:	0W	120V:	N/A
	0W N/A	120V: 208V:	N/A N/A
Watts: Shape/Size: Base:			
Shape/Size: Base:	N/A	208V:	N/A
Shape/Size:	N/A N/A	208V: 240V:	N/A N/A
Shape/Size: Base: ANSI:	N/A N/A N/A	208V: 240V: 277V:	N/A N/A N/A

Listings	Gauge:	Anchor Bolt:	
CSA Listed:	7	Galvanized anchor bolts and galvanized hardware and	
Suitable for wet locations.	Wall Thickness:	anchor bolt template. All bolts have a 3" hook.	
Construction	3/16"	Anchor Bolt Templates:	
Shaft:	Shaft Size:	WARNING Template must be printed on 11" x 17" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available.	
46,000 p.s.i. minimum yield.	5"		
Hand Holes:	Hand Hole Dimensions:		
Reinforced with grounding lug and removable cover.	3" x 5"	Pre-Shipped Anchor Bolts:	
Base Plates:	Bolt Circle:	Bolts can be pre-shipped upon request for additional freight charge.	
36,000 p.s.i. minimum yield.	11"	MaxEPA's/Max Weights:	
Shipping Protection:	Base Dimension:	70MPH 12.1 ft /300 lb	
All poles are shipped in individual corrugated cartons	11"	80MPH 7.8 ft /195 lb	
to prevent finish damage.	Weight:	90MPH 4.7 ft_/115 lb	
Color:	433 lbs.	100MPH 2.4 ft_/60 lb	
Bronze powder coating.	403 105.	110MPH 0.7 ft_/15 lb.	
Height:		Other	
30 FT.		Terms of Sale:	
		Pole Terms of Sale is available .	

Features

Designed for ground mounting Heavy duty TGIC polyester coating Reinforced hand holes with grounding lug and removable cover for easy wiring access Anchor Bolt Kit includes pole cap and base cover (sold separately) Custom manufactured for each application