

Technical Specifications (continued)

Construction

Cold Weather Starting:

The minimum starting temperature is -20°C (-4°F)

Maximum Ambient Temperature:

Suitable for use in up to 50°C (122°F)

Lens:

Polycarbonate lens

Reflector:

Polycarbonate

Housing:

Die-cast aluminum

Mounting:

Comes standard with V-hooks for chain mounting. Accessories available for pendant and surface mounting (purchased separately).

Finish:

Formulated for high durability and long-lasting color

Green Technology:

Mercury and UV free. RoHS-compliant components.

Other

5 Yr Limited Warranty:

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.


Note:

All values are typical (tolerance +/- 10%)

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

- 100,000-Hour LED lifespan
- DLC Premium Listed
- 0-10V dimming standard
- 5-Year, Limited Warranty

Ordering Matrix

Family	Size/Wattages	Color Temp	Mounting	Finish	Voltage	Options
RBAY17	L	Blank = 5000K/4000K/3500K	Blank = V-Hook/Chain	Blank = White	/480	Blank = No Option /E = Battery Backup ¹
	S = 14" (130/100/80W) M = 20" (260/220/160W) L = 39" (400/320/260W)				Blank = 120-277V, 0-10V Dimming /480 = 480V, 0-10V Dimming	

¹ Available only for 120-277V models