T5HE-13-48G-835-DIR

Project:	Туре:	Prepared By:	Date:
		Easy to inst instructions 50,000 hou Rated for u locations Diffused fro Compatible check Com Instant on f Environmen NSF Listed:	
LISTED	UPC: 0		DLC Listed
-	NSE F	C	DLC Listed
Performance	NSE F	C	
Performance Product Type:	NSF. F Dimmable: Yes L70 Lifespa	i۳:	Lens Finish:
Performance Product Type:	NSF Dimmable: Yes L70 Lifespa 50,000-Hour	EED lifespan based on IES LM-80	Lens Finish: Frosted Base Type: G5
Performance Product Type: Linear Input Wattage: 13W	NSF Dimmable: Yes L70 Lifespa 50,000-Hour	An: LED lifespan based on IES LM-80 M-21 calculations	Lens Finish: Frosted Base Type: G5 Beam Angle:
Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal):	NSF Dimmable: Yes L70 Lifespa 50,000-Hour results and TI Construct	An: LED lifespan based on IES LM-80 M-21 calculations	Lens Finish: Frosted Base Type: G5 Beam Angle: 160°
Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal): 1950	Dimmable: Yes L70 Lifespa 50,000-Hour results and T	An: LED lifespan based on IES LM-80 M-21 calculations	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical
Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal): 1950 Efficacy:	NSF Dimmable: Yes L70 Lifespa 50,000-Hour results and TI Construct Length Nor 4FT	An: LED lifespan based on IES LM-80 M-21 calculations ion minal:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD:
Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal): 1950 Efficacy: 150 lm/W	NSF Dimmable: Yes L70 Lifespa 50,000-Hour results and TI Constructi Length Nor	An: LED lifespan based on IES LM-80 M-21 calculations ion minal:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20%
Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal): 1950 Efficacy: 150 lm/W Color Accuracy:	NSF Dimmable: Yes L70 Lifespa 50,000-Hour results and TI Construct Length Nor 4FT Bulb Shape	An: LED lifespan based on IES LM-80 M-21 calculations tion minal:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20% Power Factor:
Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal): 1950 Efficacy: 150 lm/W Color Accuracy: 80	NSF Dimmable: Yes L70 Lifespa 50,000-Hour results and TI Constructi Length Nor 4FT Bulb Shape T5	An: LED lifespan based on IES LM-80 M-21 calculations tion minal:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20%
Technical Specification Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal): 1950 Efficacy: 150 lm/W Color Accuracy: 80 Color Temperature: 3500K	NSF Dimmable: Yes L70 Lifespa 50,000-Hour results and TI Constructi Length Nor 4FT Bulb Shape T5 Enclosure I	An: LED lifespan based on IES LM-80 M-21 calculations ion ninal: :: Material:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20% Power Factor:

RAB

Technical Specifications (continued)

Electrical

Operating Temperature:

-20°C-45°C

Input Voltage:

120-277V

Operating Frequency:

50 / 60 Hz

Installation

Installation Method:

UL TYPE A, Plug and Play

Other

Equivalency:

F28T5

Technology EQ:

Fluorescent

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

Safety Listing:

UL Listed

Environment/Fixture Rating:

Damp / Enclosed

NSF Listing:

NSF/ANSI Standard 2 - Food Equipment (noncontact), Splash Zone, and Non-Food Zone. (Not for Direct Food Zone without additional fixture considerations)

DLC:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. DLC Product Code: P80E6RNW

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

