T5HE-13-48G-850-DIR

Project:	Туре:	Prepared By:	Date:
		Easy to inst instructions 50,000 hou Rated for us locations Diffused fro Compatible check Comp Instant on f Environmer NSF Listed: (Not for Dir	
LISTED	UPC: 0	FC	DLC Listed
USTED LISTED Technical Specificati Performance	NSF	FC	Lens Finish:
Technical Specificati Performance	ions Dimmable Yes	e:	Lens Finish: Frosted
Technical Specificati Performance Product Type:	ions Dimmable Yes L70 Lifes	FCC e: pan:	Lens Finish: Frosted Base Type:
Technical Specificati Performance Product Type: _inear	ions Dimmable Yes L70 Lifes 50,000-Hou	e: pan: ur LED lifespan based on IES LM-80	Lens Finish: Frosted Base Type: G5
Technical Specificati Performance Product Type: Linear Input Wattage: 13W	ions Dimmable Yes L70 Lifes 50,000-Hou results and	e: pan: ur LED lifespan based on IES LM-80 TM-21 calculations	Lens Finish: Frosted Base Type: G5 Beam Angle:
Technical Specificati Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal):	ions Dimmable Yes L70 Lifes 50,000-Hou results and Construct	e: pan: ur LED lifespan based on IES LM-80 TM-21 calculations ction	Lens Finish: Frosted Base Type: G5 Beam Angle: 160°
Technical Specificati Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal): 2000	ions Dimmable Yes L70 Lifes 50,000-Hou results and Construe Length N	e: pan: ur LED lifespan based on IES LM-80 TM-21 calculations ction	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical
Technical Specificati Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal): 2000 Efficacy:	ions Dimmable Yes L70 Lifes 50,000-Hou results and Construct Length N 4FT	e: pan: ur LED lifespan based on IES LM-80 TM-21 calculations ction	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD:
Technical Specificati Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal): 2000 Efficacy: 154 lm/W	ions Dimmable Yes L70 Lifes 50,000-Hou results and Construct Length N 4FT Bulb Sha	e: pan: ur LED lifespan based on IES LM-80 TM-21 calculations ction	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20%
Technical Specificati Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal): 2000 Efficacy: 154 lm/W Color Accuracy:	ions Dimmable Yes L70 Lifes 50,000-Hou results and Construct Length N 4FT Bulb Sha T5	e: pan: ur LED lifespan based on IES LM-80 TM-21 calculations ction ominal: pe:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20% Power Factor:
Technical Specificati Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal): 2000 Efficacy: 154 Im/W Color Accuracy: 80	ions Dimmable Yes L70 Lifes 50,000-Hou results and Construct Length N 4FT Bulb Sha T5 Enclosure	e: pan: ur LED lifespan based on IES LM-80 TM-21 calculations ction	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20%
Technical Specificati Performance Product Type: Linear Input Wattage: 13W Lumens (Nominal): 2000 Efficacy: 154 lm/W	ions Dimmable Yes L70 Lifes 50,000-Hou results and Construct Length N 4FT Bulb Sha T5	e: pan: ur LED lifespan based on IES LM-80 TM-21 calculations ction lominal: pe: e Material:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20% Power Factor:

RAB

Technical Specifications (continued)

Electrical

Operating Temperature:

-20°C-45°C

Input Voltage:

120-277V

Operating Frequency:

50 / 60 Hz

Installation

Installation Method:

UL TYPE A, Plug and Play

Other

Equivalency:

F28T5

Technology EQ:

Fluorescent

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

Safety Listing:

UL Listed

Environment/Fixture Rating:

Damp / Enclosed

NSF Listing:

NSF/ANSI Standard 2 - Food Equipment (noncontact), Splash Zone, and Non-Food Zone. (Not for Direct Food Zone without additional fixture considerations)

DLC:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. DLC Product Code: PLSRFI1S

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

