# T5HO-18-36G-850-DIR

Project:	Туре:	Prepared By:	Date:
		Direct Deale	Features and Benefits
			cement for conventional fluorescent F54T5/HO tubes all plug and play that requires no rewiring, no tools, no
		50,000 hour	
			e in enclosed and open fixtures in dry or damp
		Diffused from	sted lens will maintain the same light quality over time
E		Compatible Please chec	with most program start electronic T5HO ballasts, k Compatibility List. Do Not Install on T5HE Ballasts
		Instant on fu	ull brightness
		Environmen	tally friendly, no mercury used
			NSF/ANSI Standard 2 - Food Equipment - Splash Zone ect Food Zone without additional fixture considerations
	UPC: 0		LC Listed
LISTED		C	
-	NSF. F		
Performance	NSF F		Lens Finish:
Performance Product Type:	NSF F	:	<b>Lens Finish:</b> Frosted
Performance Product Type:	NSF S Dimmable Yes L70 Lifesp	: an:	Lens Finish: Frosted Base Type:
Performance Product Type: Linear	NSF S Dimmable Yes L70 Lifesp 50,000-Hour	:	<b>Lens Finish:</b> Frosted <b>Base Type:</b> G5
Performance Product Type: Linear Input Wattage: 18W	NSF S Dimmable Yes L70 Lifesp 50,000-Hour	<b>an:</b> LED lifespan based on IES LM-80 'M-21 calculations	Lens Finish: Frosted Base Type: G5 Beam Angle:
Performance Product Type: Linear Input Wattage: 18W Lumens (Nominal):	NSF Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct	: an: LED lifespan based on IES LM-80 M-21 calculations tion	Lens Finish: Frosted Base Type: G5 Beam Angle: 160°
Performance Product Type: Linear Input Wattage: 18W Lumens (Nominal): 2300	NSF Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct Length No	: an: LED lifespan based on IES LM-80 M-21 calculations tion	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical
Performance Product Type: Linear Input Wattage: 18W Lumens (Nominal): 2300 Efficacy:	NSF Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct Length No 3FT	an: LED lifespan based on IES LM-80 TM-21 calculations tion minal:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD:
Performance Product Type: Linear Input Wattage: 18W Lumens (Nominal): 2300 Efficacy: 128 Im/W	NSF Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct Length No	an: LED lifespan based on IES LM-80 TM-21 calculations tion minal:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20%
Performance Product Type: Linear Input Wattage: 18W Lumens (Nominal): 2300 Efficacy: 128 lm/W Color Accuracy:	NSF Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct Length No 3FT Bulb Shap	an: LED lifespan based on IES LM-80 TM-21 calculations tion minal: e:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20% Power Factor:
Efficacy: 128 Im/W Color Accuracy: 80 Color Temperature:	NSF Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct Length No 3FT Bulb Shap T5	an: LED lifespan based on IES LM-80 TM-21 calculations tion minal: e:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20%
Performance Product Type: Linear Input Wattage: 18W Lumens (Nominal): 2300 Efficacy: 128 lm/W Color Accuracy:	NSF Dimmable Yes L70 Lifesp 50,000-Hour results and T Construct Length No 3FT Bulb Shap T5 Enclosure	: an: LED lifespan based on IES LM-80 TM-21 calculations tion minal: e: Material:	Lens Finish: Frosted Base Type: G5 Beam Angle: 160° Electrical THD: ≤20% Power Factor:

RAB

## Technical Specifications (continued)

#### **Electrical**

**Operating Temperature:** 

-20°C-45°C

Input Voltage:

120-277V

**Operating Frequency:** 

50 / 60 Hz

## Installation

Installation Method:

UL TYPE A, Plug and Play

#### Other

Equivalency:

F39T5/HO

## Technology EQ:

Fluorescent

## Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

#### Compliance

Safety Listing:

UL Listed

## **Environment/Fixture Rating:**

Damp / Enclosed

#### **NSF Listing:**

NSF/ANSI Standard 2 - Food Equipment (noncontact), Splash Zone, and Non-Food Zone. (Not for Direct Food Zone without additional fixture considerations)

#### **RoHS:**

Mercury and UV free. RoHS-compliant components.

#### FCC:

Complies with Part 15 of the FCC Rules

