



Replace existing fluorescent tubes. Glass and plastic models available.  
 Color: Frosted white                      Weight: 0.5 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Watts	11W	Input Voltage	Ballast Dependent
Color Temp	4000K (Cool White)	Power Factor	Ballast Dependent
Lumens	1,800	Flicker	N/A
Efficacy	171.4 LPW	THDi	<25%
Color Accuracy	80 CRI	R9	
L70 Accuracy	50,000		

## Technical Specifications

### Listings

**UL Listed:**

Yes

**NSF Listing:**

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones

**FCC:**

Yes

**Rohs:**

Yes

**DLC Qualified:**

Yes

**DLC Listed:**

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. DLC Product Code: PC31UUKD

### Description

**Lamp Type:**

Linear T8

**Bulb Type:**

T8

**Base Type:**

G13, Medium Bipin

**Length:**

4ft

**Material:**

Glass

### LED Characteristics

**Installation Type:**

Type A, Plug and Play

### Lifespan:

50,000-hour LED lifespan based on IES LM-70 results

### Construction

**Operating Temperature:**

-20 - 45°C

**Environment Friendly:**

No mercury used

### Other

**Equivalent:**

32W Fluorescent T8

**Warranty:**


5-years

### Optical

**Beam Angle:**

180°

## Dimensions



## Features

- FLUORESCENT REPLACEMENT - Replacement for conventional fluorescent T8 linear tubes
- EASY TO INSTALL - Simply plug and play No rewiring, no tools, no instructions
- 50,000-HOUR LIFESPAN - Lasts 1.6x longer than conventional fluorescent tubes
- ENCLOSED FIXTURE RATED - May be used in enclosed and open fixtures
- DIFFUSION COATING - Will maintain the same light quality over time and won't yellow, shrink, or wrinkle
- BALLAST COMPATIBLE - Please check Compatibility List
- SAVE ENERGY AND MONEY - Approximately 40% more efficient than conventional T8 lamps
- INSTANT ON - No warmup time required, full brightness instantly
- MERCURY FREE - Environmentally friendly vs fluorescent technologies

## Ordering Matrix

Family	Lamp Power	Length	Material	Base Type	CRI/Color Temp	Installation Type
T8	10.5	48	G	C	8	40
	6 = 17W 8 = 25W 12 = 32W 15 = 32W	24 = 2 ft. 36 = 3 ft. 48 = 4 ft.	G = Glass P = Plastic	Blank = G13	830 = 3000K 835 = 3500K 840 = 4000K 850 = 5000K	DIR = Ballast Compatible