T8-12-48G-830-DIR

RAB Lamps

	Project:	Project:		Туре:	
	Prepare	d By:	Date:		
RAB	Driver Info Watts:	12W	LED Info Input Voltage: Balla		
Replace existing fluorescent tubes. Glass and plastic mo	L70 Accurac	3000K (Warm White) 1,650 138 LPW 82 CRI : 50,000	Power Factor: Balla Flicker: N/A THDi: <20%		
Color: White We	eight: 0.4 lbs				
Technical Specifications					
Listings	Base Type:	MOD (inches)	:		
UL Listed:	G13, Medium Bipin	1.09"			
Yes	Dimmable:	Other			
NSF:	No	Equivalent:			
Complies with NSF	Length:	32W Fluorescent	t T8		
FCC:	4ft	Warranty:			
Yes	Material:	5 years			
Rohs:	Glass	Optical			
Yes	LED Characteristics	Beam Angle:			
CEC Status:	Installation Type:	240°			
Lawful for sale in California	Type A, Plug and Play	Shipping Info	rmation		
DLC Qualified:	Lifespan:	Case Qty:			
Yes	50,000-hour LED lifespan based on IES LM-70 results	25			
DLC Listed:	Construction	Case Dimensi	ons:		
This product is on the Design Lights Consortium (DLC)	Operating Temperature:	49.2 x 7.87 x 7.28			
Qualified Products List and is eligible for rebates from DLC Member Utilities.	-20 - 40°C	Pallet Quantity of Pieces:			
DLC Product Code: PR9A4GKW	Bare Lamp Illuminated Length (inches):	750			
Description	47.22"	Pallet Dimensions:			
Lamp Type:	MOL (inches):	49.21 x 39.37 x 4			
Linear T8	47.5"				
Bulb Type:					
T8					

T8-12-48G-830-DIR



Replacement for conventional Fluorescent T8 linear tubes

Plug and Play, no rewiring, no tools, no instructions

Compatible with most commercial ballasts, refer to our published compatibility guide

Suitable for use in enclosed and open fixtures

Approximately 40% More Energy Efficient that Standard T8 Lamps

Start up instantly, no flicker or hum like conventional fluorescent tubes

Environmentally friendly, no mercury used and are easy to recycle

