## T8-12-48G-835-HYB


		Project:		Туре:
RAB		Prepared B	3y:	Date:
Hybrid A/B Tubes can be used as a plug ar Type B) retrofit. This allows for maximum ir SKUs need to stock. Color: White		Color Temp		LED Info Input Voltage Ballast Dependent Power Factor >0.9 Flicker N/A THDi N/A R9
-				
Technical Specifications	Efficacy:		Beam Angle:	
Technical Specifications Product Type:	150 lm/W	2	210°	
Technical Specifications Product Type: Linear	150 lm/W Color Temperature:	2 V	210° <b>Warranty:</b>	
Technical Specifications Product Type: Linear Bulb Shape:	150 lm/W Color Temperature: 3500K Neutral White	2 V 5	210° <b>Warranty:</b> 5-Year, No-Comp	promise Warranty
Technical Specifications Product Type: Linear Bulb Shape: T8	150 lm/W Color Temperature: 3500K Neutral White CRI:	2 V 5	210° <b>Warranty:</b> 5-Year, No-Comp nstallation Tyj	be:
Technical Specifications Product Type: Linear Bulb Shape: T8 Nominal Length:	150 lm/W Color Temperature: 3500K Neutral White CRI: 80	2 V 5 II F	210° <b>Warranty:</b> 5-Year, No-Comp <b>nstallation Tyj</b> Hybrid, Works wit	<b>be:</b> h or without Ballast
Technical Specifications Product Type: Linear Bulb Shape: T8 Nominal Length: 4FT	150 lm/W Color Temperature: 3500K Neutral White CRI: 80 Base Type:	2 V 5 II F	210° <b>Warranty:</b> 5-Year, No-Comp <b>nstallation Tyj</b> Hybrid, Works wit For Use in Eme	be:
Technical Specifications Product Type: Linear Bulb Shape: T8 Nominal Length: 4FT Finish:	150 lm/W Color Temperature: 3500K Neutral White CRI: 80 Base Type: G13	2 V 5 I I F F N	210° Warranty: 5-Year, No-Comp nstallation Tyj Hybrid, Works wit For Use in Eme No	be: h or without Ballast ergency Fixtures:
Technical Specifications Product Type: Linear Bulb Shape: T8 Nominal Length: 4FT Finish: Frosted	150 lm/W Color Temperature: 3500K Neutral White CRI: 80 Base Type: G13 L70 Lifespan:	2 5 1 1 7 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	210° Warranty: 5-Year, No-Comp nstallation Typ Hybrid, Works wit For Use in Eme No For Use Outdo	<b>be:</b> h or without Ballast
Technical Specifications Product Type: Linear Bulb Shape: T8 Nominal Length: 4FT Finish: Frosted Wattage:	150 lm/W Color Temperature: 3500K Neutral White CRI: 80 Base Type: G13 L70 Lifespan: 50,000 hours	2 5 1 1 7 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	210° Warranty: 5-Year, No-Comp nstallation Tyj Hybrid, Works wit For Use in Eme	be: h or without Ballast ergency Fixtures:
Technical Specifications Product Type: Linear Bulb Shape: T8 Nominal Length: 4FT Finish: Frosted Wattage: 12W	150 lm/W Color Temperature: 3500K Neutral White CRI: 80 Base Type: G13 L70 Lifespan: 50,000 hours Operating Temperature:	2 5 1 1 7 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	210° Warranty: 5-Year, No-Comp nstallation Typ Hybrid, Works wit For Use in Eme No For Use Outdo	be: h or without Ballast ergency Fixtures:
Technical Specifications Product Type: Linear Bulb Shape: T8 Nominal Length: 4FT Finish: Frosted Wattage: 12W Wattage Equivalency:	150 lm/W Color Temperature: 3500K Neutral White CRI: 80 Base Type: G13 L70 Lifespan: 50,000 hours Operating Temperature: -25°C - 45°C	2 5 1 1 7 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	210° Warranty: 5-Year, No-Comp nstallation Typ Hybrid, Works wit For Use in Eme No For Use Outdo	be: h or without Ballast ergency Fixtures:
Technical Specifications Technical Specifications Product Type: Linear Bulb Shape: T8 Nominal Length: 4FT Finish: Frosted Wattage: 12W Wattage Equivalency: 32W Fluorescent Typical Lumen Output:	150 lm/W Color Temperature: 3500K Neutral White CRI: 80 Base Type: G13 L70 Lifespan: 50,000 hours Operating Temperature:	2 5 1 1 7 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	210° Warranty: 5-Year, No-Comp nstallation Typ Hybrid, Works wit For Use in Eme No For Use Outdo	be: h or without Ballast ergency Fixtures:

# T8-12-48G-835-HYB

## Technical Specifications (continued)

Electrical Characteristics	Input Current @ 277V:	NSF Listing:		
Input Voltage:	Ballast Dependent	Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones		
Ballast Dependent	THDi:			
Power Factor:	<25%	CEC Status: Lawful for sale in California		
>0.9	Listings			
Operating Frequency:	UL Listed:			
Ballast Dependent	Yes			
Input Current @ 120V:	UL Classified:			
Ballast Dependent	Yes			

#### Dimensions



### Features

FLUORESCENT REPLACEMENT - Replace conventional fluorescent T8 linear tubes.

TYPE A/B Glass Hybrid - is both Ballast Bypass and Ballast Compatible.

COMPATIBLE with common commercial instant start ballasts.

50,000-HOUR LIFESPAN - Lasts 1.6x longer than conventional fluorescent tubes.

ENCLOSED FIXTURE RATED - May be used in enclosed and open fixtures.

DIFFUSION COATING - Will maintain the same light quality over time and woni  $_{2}t$  yellow, shrink, or wrinkle.

HIGHLY EFFICIENT led tube delivers greater than 150 lm/W.

SAVE ENERGY AND MONEY - Approximately 40% more efficient than conventional T8 lamps.

MERCURY FREE - Environmentally friendly vs fluorescent technologies.