## T8-12-48P-850-DIR

RAB<sup>®</sup> Lamps

	Project:		Туре:
	Prepared	By:	Date:
RAB	Driver Info		LED Info
	Watts: Color Temp: Lumens: Efficacy: Color Accura L70 Accuracy	1,800 150 LPW cy: 80 CRI	Input Voltage: Ballast Dependent Power Factor: Ballast Dependent Flicker: N/A THDi: <20%
Replace existing fluorescent tubes. Glass and plastic mo Color: White We	odels available. eight: 0.3 lbs		
Technical Specifications			
Listings	Base Type:	MOD (inches):	
UL Listed:	G13, Medium Bipin	0.5"	
Yes	Dimmable:	Other	
NSF:	No	Equivalent:	
Complies with NSF	Length:	32W Fluorescent T	8
FCC:	4ft	Warranty:	
Yes	Material:	5 years	
Rohs:	Plastic	Optical	
Yes	LED Characteristics	Beam Angle:	
CEC Status:	Installation Type:	160°	
Lawful for sale in California	Type A, Plug and Play	Shipping Inform	nation
DLC Qualified:	Lifespan:	Case Qty:	
Yes	50,000-hour LED lifespan based on IES LM-70 results	25	
DLC Listed:	Construction	Case Dimensions:	
This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from	<b>Operating Temperature:</b> 48.66 x 6.69 x 6.61		
DLC Member Utilities.	-20 - 40°C	Pallet Quantity	of Pieces:
DLC Product Code: PVMFIEYB	Bare Lamp Illuminated Length (inches):	750	
Description			

Description

### Lamp Type: Linear T8

Bulb Type:

Т8


#### MOL (inches): 47.5"

47.22"

Pallet Dimensions:

49.21 x 39.37 x 45.28

# T8-12-48P-850-DIR



#### Features

Replacement for conventional Fluorescent T8 linear tubes

Plug and Play, no rewiring, no tools, no instructions

Compatible with most commercial ballasts, refer to our published compatibility guide

Suitable for use in enclosed and open fixtures

Approximately 40% More Energy Efficient that Standard T8 Lamps

Start up instantly, no flicker or hum like conventional fluorescent tubes

Environmentally friendly, no mercury used and are easy to recycle