## T8-15-48G-830-DIR

RAB Lamps

	Project:		Туре:	
	Prepared	By:	Date:	
Replace existing fluorescent tubes. Glass and plastic mo Color: White We	Driver Info Watts: Color Temp: Lumens: Efficacy: Color Accuracy: L70 Accuracy	15W 3000K (Warm White) 2,000 133 LPW 82 CRI 7: 50,000		Ballast Dependent Ballast Dependent N/A <20%
Technical Specifications				
Listings	Base Type:	MOD (inches):		
UL Listed:	G13, Medium Bipin	1.09"		
Yes	Dimmable:	Other		
NSF:	No	Equivalent:		
Complies with NSF	Length:	- 32W Fluorescent	Т8	
FCC:	4ft	Warranty:		
Yes	Material:	5 years		
Rohs:	Glass	Optical		
Yes	LED Characteristics	Beam Angle:		
CEC Status:	Installation Type:	240°		
Lawful for sale in California	Type A, Plug and Play	Shipping Infor	mation	
DLC Qualified:	Lifespan:	Case Qty:		
Yes	50,000-hour LED lifespan based on IES LM-70 results	25		
DLC Listed:	Construction	Case Dimensions:		
This product is on the Design Lights Consortium (DLC)	Operating Temperature:	49.2 x 7.87 x 7.28		
Qualified Products List and is eligible for rebates from DLC Member Utilities.	-20 - 40°C	Pallet Quantity of Pieces:		
DLC Product Code: PP9D27J7	Bare Lamp Illuminated Length (inches):	750		
Description	47.22"	Pallet Dimensions:		
Lamp Type:	MOL (inches):	49.21 x 39.37 x 4	8.82	
Linear T8	47.5"			
Bulb Type:				
Т8				

## T8-15-48G-830-DIR



Replacement for conventional Fluorescent T8 linear tubes

Plug and Play, no rewiring, no tools, no instructions

Compatible with most commercial ballasts, refer to our published compatibility guide

Suitable for use in enclosed and open fixtures

Approximately 40% More Energy Efficient that Standard T8 Lamps

Start up instantly, no flicker or hum like conventional fluorescent tubes

Environmentally friendly, no mercury used and are easy to recycle

