## T8-17-48G-835-DE-BYP

RAB Lamps



Project: Prepared By: Driver Info		Type: Date: LED Info					
				Watts:	17W	Input Voltage:	120-277V
				Color Temp:	3500K (Neutral White)	Power Factor: Flicker:	0.9 N/A
Lumens:	2,100	THDi:	<20%				
Efficacy:	124 LPW						
Color Accuracy:	82 CRI						

Replace conventional T5/T8/T12 fluorescent tubes. Double-ended line voltage wiring. Works with shunted and non-shunted sockets - no need to change sockets.

Weight: 0.6 lbs

Color: White

Technical Specifications		
Listings	Bulb Type:	MOD (inches):
UL Recognized:	Т8	1.02"
Yes	Base Type:	Other
UL Classified:	G13, Medium Bipin	Equivalent:
Yes	Dimmable:	32W Fluorescent T8
NSF:	No	Warranty:
Complies with NSF	Length:	5 years
FCC:	4ft	Optical
/es	Material:	Beam Angle:
Rohs:	Glass	240°
Yes	LED Characteristics	Shipping Information
CEC Status:	Installation Type:	Case Qty:
awful for sale in California	Type B, Ballast Bypass, Double Ended Wire	25
DLC Qualified:	Lifespan:	Case Dimensions:
/es	50,000-hour LED lifespan based on IES LM-70 results	48.82 x 5.91 x 5.91
DLC Listed:	Construction	Pallet Quantity of Pieces:
This product is on the Design Lights Consortium (DLC)	Operating Temperature:	1050
Qualified Products List and is eligible for rebates from DLC Member Utilities.	-20 - 40°C	Pallet Dimensions:
DLC Product Code: PY1WPW83	MOL (inches):	49.21 x 39.37 x 46.06
Description	47.78"	
Lamp Type:		
Linear T8		

## T8-17-48G-835-DE-BYP



Internal Driver eliminates the need for external ballasts or drivers

Can be wired either using Single Ended or Double Ended wiring method for maximum flexibility in the field and simplifies stocking multiple skus

Suitable for use in enclosed and open fixtures

Approximately 40% More Energy Efficient that Standard T8 Lamps

Start up instantly, no flicker or hum like conventional fluorescent tubes

Environmentally friendly, no mercury used and are easy to recycle

