

T8-52-48G-840-EXT-4L-DIM



Replace existing T8/T12 fluorescent tubes. Replace existing ballast with a dedicated LED driver. Sold in 2-lamp and 4-lamp kits.

Color: White

Weight: 1.0 lbs

Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Watts:	13W	Input Voltage:	120-277V
Color Temp:	4000K (Cool White)	Power Factor:	0.9
Lumens:	1,650	Flicker:	N/A
Efficacy:	127 LPW	THDi:	<20%
Color Accuracy:	80 CRI		
L70 Accuracy:	50,000		

Technical Specifications

Listings

ETL Qualified:

Yes

NSF:

Complies with NSF

FCC:

Yes

Rohs:

Yes

CEC Status:

Lawful for sale in California

DLC Qualified:

Yes

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.
DLC Product Code: P3SZW6AY

Description

Dimmable:

Yes

Lamp Type:

Linear T8

Bulb Type:

T8

Base Type:

G13, Medium Bipin

LED Characteristics

Installation Type:

Type C, External Driver

Lifespan:

50,000-hour LED lifespan based on IES LM-70 results

Construction

Operating Temperature:

-20 - 40°C

Bare Lamp Illuminated Length (inches):

47.22"

MOL (inches):

47.5"

MOD (inches):

1.09"

Other

Equivalent:

32W Fluorescent T8

Warranty:

5 years

Optical

Beam Angle:

240°

Shipping Information

Case Qty:

6

Case Dimensions:

48.937 x 17.441 x 5.984

Pallet Quantity of Pieces:


84

Pallet Dimensions:

49.213 x 39.370 x 47.008

T8-52-48G-840-EXT-4L-DIM

Dimensions



Features

- Replacement for conventional Fluorescent linear tubes
- Type C Application for Custom Installations and Maximum Efficiency
- Suitable for use in enclosed and open fixtures
- Approximately 40% More Energy Efficient than Standard T8 Lamps
- Start up instantly, no flicker or hum like conventional fluorescent tubes
- Environmentally friendly, no mercury used and are easy to recycle