T8-7-24GC-835-DIR





Project: Type: Prepared By: Date:

Replace existing T8 fluorescent tubes. Plug and Play tubes, no rewiring required with a shatter resistant coated glass construction

> Color: White Weight: 0.3 lbs

LED Info Driver Info

Watts 7.00W 3500K (Neutral Color Temp White) Lumens 1,050

Power Factor Ballast Dependent **Ballast Dependent** Flicker THDi N/A

Input Voltage Ballast Dependent

150 LPW

Color Accuracy 80 CRI

L70 Accuracy 50,000

Efficacy

Technical Specifications

Technical Specifications

Product Type:

Linear

Bulb Shape:

T8

Nominal Length:

2FT Finish:

Frosted

Wattage:

Wattage Equivalency:

Typical Lumen Output: 1050

17W Fluorescent

Efficacy:

150 lm/W

Color Temperature:

3500K Neutral White

CRI: 80

Base Type:

G13

L70 Lifespan:

50,000 hours

Operating Temperature: -20°C - 45°C

Dimmable:

No

Beam Angle:

180°

Warranty:

5-Year, No-Compromise Warranty

Installation Type: Type A, Plug and Play

For Use in Emergency Fixtures:

For Use Outdoors in Open Fixtures:

No

T8-7-24GC-835-DIR



Technical Specifications (continued)

Electrical Characteristics

Input Voltage:

Ballast Dependent

Power Factor:

Ballast Dependent

Operating Frequency:

Ballast Dependent

Input Current @ 120V:

Ballast Dependent

Input Current @ 277V:

Ballast Dependent

Flicker:

Ballast Dependent

THDi: ≤25%

Listings
UL Listed:

Yes

NSF Listing:

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones

CEC Status:

Lawful for sale in California