T8-7-24GC-835-SD-BYP





Replace conventional T8/T12 fluorescent tubes. Capable of single- or double-ended wiring for maximum in-the-field flexibility. Shatter resistant coated glass construction.

Color: White Weight: 0.3 lbs

Project:	Туре:
Prepared By:	Date:

Driver Info LED Info

Beam Angle:

180°

Watts 7.00W
Color Temp 3500K (Neutral White)

 3500K (Neutral White)
 Power Factor >0.9

 Flicker
 N/A

 THDi
 N/A

Input Voltage 120-277

Efficacy 135.7 LPW Color Accuracy 80 CRI

Lumens

L70 Accuracy 50,000

Technical Specifications

Technical Specifications

Product Type: 130 lm/W

Linear Color Temperature: Warranty:

Efficacy:

Bulb Shape: 3500K Neutral White 5-Year, No-Compromise Warranty

T8 CRI: Installation Type:

Nominal Length: 80 Type B, Single or Double Ended wiring

2FT Base Type: For Use in Emergency Fixtures:

Finish: G13 N

Frosted L70 Lifespan: For Use Outdoors in Open Fixtures:

Wattage: 50,000 hours No


7W Operating Temperature: Wattage Equivalency: -20°C - 45°C

17W Fluorescent Dimmable:

Typical Lumen Output: No

950

T8-7-24GC-835-SD-BYP



Technical Specifications (continued)

Electrical Characteristics

Input Voltage:

120-277V

Power Factor:

>0.9

Operating Frequency:

50 / 60 Hz

Input Current @ 120V:

68mA

Input Current @ 277V:

29mA **THDi:** ≤25%

Listings

UL Recognized:

Yes

UL Classified:

Yes

NSF Listing:

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones

CEC Status:

Lawful for sale in California