



Replace existing T8 fluorescent tubes. Plug and Play tubes, no rewiring required with a shatter resistant coated glass construction

Color: White

Weight: 0.3 lbs

**Project:**

**Type:**

**Prepared By:**

**Date:**

**Driver Info**

**LED Info**

Watts	7.00W	Input Voltage	Ballast Dependent
Color Temp	5000K (Daylight)	Power Factor	Ballast Dependent
Lumens	1,050	Flicker	Ballast Dependent
Efficacy	150 LPW	THDi	N/A
Color Accuracy	80 CRI	R9	
L70 Accuracy	50,000		

## Technical Specifications

### Technical Specifications

**Product Type:**

Linear

**Bulb Shape:**

T8

**Nominal Length:**

2FT

**Finish:**

Frosted

**Wattage:**

7W

**Wattage Equivalency:**

17W Fluorescent

**Typical Lumen Output:**

1050

**Efficacy:**

150 lm/W

**Color Temperature:**

5000K Daylight

**CRI:**

80

**Base Type:**

G13

**L70 Lifespan:**

50,000 hours

**Operating Temperature:**

-20°C - 45°C

**Dimmable:**

No

**Beam Angle:**

180°

**Warranty:**

5-Year, No-Compromise Warranty

**Installation Type:**

Type A, Plug and Play

**For Use in Emergency Fixtures:**

No

**For Use Outdoors in Open Fixtures:**

No

## Technical Specifications (continued)

### Electrical Characteristics

---

**Input Voltage:**

Ballast Dependent

**Power Factor:**

Ballast Dependent

**Operating Frequency:**

Ballast Dependent

**Input Current @ 120V:**

Ballast Dependent

**Input Current @ 277V:**

Ballast Dependent

**Flicker:**

Ballast Dependent

**THDi:**

≤25%

**Listings**

---

**UL Listed:**

Yes

**NSF Listing:**

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones

**CEC Status:**

Lawful for sale in California