WPLED26MSW





LED 26W Wallpacks. Patent Pending thermal management system. 100,000 hour L70 lifespan. 5 Year Warranty.

Color: White Weight: 8.0 lbs

Project:	Туре:
Prepared By:	Date:

	LED Info	
Constant Current	Watts:	26W
0.26A	Color Temp:	5000K
N/A	Color Accuracy:	70 CRI
N/A	L70 Lifespan:	100000
N/A	Lumens:	2,662
30W	Efficacy:	90 LPW
88%		
	0.26A N/A N/A N/A 30W	Constant Current 0.26A Color Temp: N/A Color Accuracy: N/A L70 Lifespan: N/A Lumens: 30W Efficacy:

Technical Specifications

LED Characteristics

Lifespan:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

Color Consistency:

7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

Construction

IP Rating:

Ingress Protection rating of IP66 for dust and water.

Othe

Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

Optical

BUG Rating:

B1 U0 G0

BUG Rating:

B1 U0 G0

Listings

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.

DLC Product Code: P0000170J

Features

High performance LED light engine

Maintains 70% of initial lumens at 100.000 hours

Weatherproof high temperature silicone gaskets

Superior heat sinking with die cast aluminum housing and external fins

100 up to 277 Volts

5-year warranty

WPLED26MSW



dering Matrix						
Family	Watts	Color Temp	Sensor	Finish	Photocell	Dimming
WPLED						
	26 = 26W	Blank = 5000K (Cool) Y = 3000K (Warm) N = 4000K (Neutral)	Blank = No Sensor MS = Mini Sensor	Blank = Bronze W = White	Blank = No Photocell /PC = 120V Button /PCS = 120V Swivel /PC2 = 277V Button	Blank = No Dimming /D10 = Dimmable