## SATCO' NUVO

Project Name

Location

Prepared By



## **SATCO S11328**

18A21/LED/930/120V/D/GU24

Notes

General	
Status	Active
Watts	18
Incandescent Equivalent	100
Volts	120V
Shape	A21
Base	GU24
ANSI Base	GU24
Finish	White
CCT (Kelvin)	3000
Temperature	Warm White
CRI	90+
Lumens	1600
Beam Spread	220
Dimmable	Yes Dimmable
Hours Rated	25000
Lamp Type	А-Туре
Technology	LED
Electrical	
Operating Frequency	60 Hz
Operating Frequency Dimming Type	60 Hz forward phase & reverse phase
Dimming Type	forward phase & reverse phase
Dimming Type Power Factor	forward phase & reverse phase 0.97 -25C (-13F) to a maximum of +45C
Dimming Type Power Factor Operating Temperature	forward phase & reverse phase 0.97 -25C (-13F) to a maximum of +45C
Dimming Type Power Factor Operating Temperature Physical	forward phase & reverse phase 0.97 -25C (-13F) to a maximum of +45C (+113F)
Dimming Type Power Factor Operating Temperature Physical MOL	forward phase & reverse phase 0.97 -25C (-13F) to a maximum of +45C (+113F) 5.433
Dimming Type Power Factor Operating Temperature Physical MOL MOD	forward phase & reverse phase 0.97 -25C (-13F) to a maximum of +45C (+113F) 5.433 2.638
Dimming Type Power Factor Operating Temperature Physical MOL MOD Housing Color	forward phase & reverse phase 0.97 -25C (-13F) to a maximum of +45C (+113F) 5.433 2.638 WHITE
Dimming Type Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	forward phase & reverse phase 0.97 -25C (-13F) to a maximum of +45C (+113F) 5.433 2.638 WHITE
Dimming Type Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information	forward phase & reverse phase 0.97 -25C (-13F) to a maximum of +45C (+113F) 5.433 2.638 WHITE 0.364
Dimming Type Dower Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Enclosure Rating	forward phase & reverse phase 0.97 -25C (-13F) to a maximum of +45C (+113F) 5.433 2.638 WHITE 0.364 Enclosed Rated Lamp
Dimming Type Dower Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Enclosure Rating Warranty	forward phase & reverse phase 0.97 -25C (-13F) to a maximum of +45C (+113F) 5.433 2.638 WHITE 0.364 Enclosed Rated Lamp
Dimming Type Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Enclosure Rating Warranty Compliance	forward phase & reverse phase 0.97 -25C (-13F) to a maximum of +45C (+113F) 5.433 2.638 WHITE 0.364 Enclosed Rated Lamp 5 Year Limited - 10 hr per day
Dimming Type Dower Factor Derating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Enclosure Rating Warranty Compliance Safety Listing	forward phase & reverse phase 0.97 -25C (-13F) to a maximum of +45C (+113F) 5.433 2.638 WHITE 0.364 Enclosed Rated Lamp 5 Year Limited - 10 hr per day cULus

For More Information Visit: <u>https://www.satco.com/</u>

