



S11731

17T8/LED/48-CCT/EM/BP

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	17W
Color Temperature:	3500K/4000K/5000K
Length:	47.78"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	17W
Volts:	120V-277V
Fluorescent Equivalent:	32W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	White
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	3500K/4000K/5000K
CRI:	83CRI
Lumen Output:	2100L/2300L/2200L

Dimmable:	Yes-Dimmable
Beam Spread:	140D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	Ballast Bypass
Ballast Type:	Type B
Single / Dual End:	Single Ended
Tube Guard Use:	No
Shatter Proof Type:	Yes
Safety Listing:	cULus - Classified; cETLus - Listed; cRUus - Recognized Component
Technology:	LED
Material:	Aluminum

DIMENSIONS

MOL:	47.78"
MOD:	1.13"
Weight:	0.99

LISTINGS

Safety Listing:	cULus - Classified; cETLus - Listed; cRUus - Recognized Component
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-MASCZT
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	CN/US - E335148; CN/US - E356817; ETL - 4005203
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923117312	Inner UPC:	20045923117316	Case UPC:	10045923117319
Each Quantity:	1	Inner Quantity:	0	Case Quantity:	20
Each Dimensions:	0.00 x 0.00 x 0.00"	Inner Dimensions:	0.00 x 0.00 x 0.00"	Case Dimensions:	49.00 x 11.00 x 6.50"

116 Neardana Blvd. Brentwood, NY 11717 PH 631-243-2022 FX 631-243-2027	Distribution Centers New York, Florida, Texas, Washington, California, Puerto Rico	National Toll Free 800-43-SATCO (800-437-2826) www.satco.com	Copyright 2023 Satco Products, Inc. All Rights Reserved July 29, 2023
---	---	---	--