



**S11740**

9.5/T8/LED/48-830/DR

**GENERAL SPECIFICATIONS**

Shape:	T8
Wattage:	9.5W
Color Temperature:	3000K
Length:	48.00"
Base:	Medium Bi Pin



**TECHNICAL SPECIFICATIONS**

Wattage:	9.5W
Volts:	120V-277V
Fluorescent Equivalent:	32W/30W/28W/25W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	Gloss
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	3000K
CRI:	82CRI
Lumen Output:	1740L

Dimmable:	Yes-Dimmable
Dimming Function:	Check Ballast MFG for Dimmer Compatibility; Only in Type A mode; Dimming range from 100 to less than or equal to 20 percent depending on dimmer control
Beam Spread:	210D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Ballasting Requirements:	Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart
Bypass / Direct:	Direct
Ballast Type:	Type A
Safety Listing:	cULus - Listed; cULus - Certified
Technology:	LED
Material:	Glass

**DIMENSIONS**

MOL:	48.00"
MOD:	1.00"
Weight:	0.42

**LISTINGS**

Safety Listing:	cULus - Listed; cULus - Certified
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PL28A453NN99
DLC Primary Use:	Replacement Lamps (plug and play) (UL Type A)
UL File Listing:	US/CN - E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

**PACKAGING**

Each UPC:	045923117404	Case UPC:	10045923117401
1 Each Quantity:	1 on Centers	Case Quantity:	25
Brentwood, NY 11717	New York, Florida,	Case Dimensions:	5.00 x 6.00 x 6.00"
Each Dimensions:	48.00 x 1.10 x 1.10"		
P	Washington,		
FX 631-243-2027	California, Puerto Rico		
		National Toll-Free	Satco Products, Inc
		800-43-SATCO	All Rights Reserved
		(800-437-2826)	May 22, 2022
		www.satco.com	