



S11747

17T8/LED/48-850/BP/DE/347V

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	17W
Color Temperature:	5000K
Length:	47.78"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	17W
Volts:	347V
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	Gloss White
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	5000K
CRI:	82CRI
Lumen Output:	2200L

Dimmable:	Non-Dimmable
Beam Spread:	210D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	Ballast Bypass
Ballast Type:	Type B
Single / Dual End:	Double Ended
Tube Guard Use:	Yes
Safety Listing:	cUL - Classified; cUL - Certified; cRU - Recognized Component
Technology:	LED
Material:	Plastic

DIMENSIONS

MOL:	47.78"
MOD:	1.00"
Weight:	0.44

LISTINGS

Safety Listing:	cUL - Classified; cUL - Certified; cRU - Recognized Component
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-WQJYVL
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	CN - E356817; CN - E335148
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes

PACKAGING

Each UPC:	045923117473
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10"

Case UPC:	10045923117470
Case Quantity:	25
Case Dimensions:	58.00 x 6.00 x 6.00"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2022
Satco Products, Inc.
All Rights Reserved
May 22, 2022