



# S11909

7W/LED/T5/865/BP

7W T5 LED; Miniature bi-pin base; 6500K; 50000 Average rated hours; 700 Lumens; 120-277V; Type B; Ballast Bypass; Double Ended Wiring



### Features

- No ballast or external driver required
- Available in 6", 9", 12", & 21"
- Direct wire 120-277V line voltage
- Double ended wiring
- NSF Approved
- PET Shatterproof coated
- 5 year Limited warranty

S11909

Replaces F13T5/D lamps

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Power Factor	Lamp Shape
S11909	045923119095	120-277	7	50/60Hz	13W	0.90	T5
Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Miniature Bi-Pin	G5	7W/LED/T5/865/BP	Non-Dimmable	Frosted	20-29/32"	0-5/8"	700
Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status
50000	6500	Daylight	80	240	-25C (-13F) to a maximum of +45C (+113F)	10	Lawful for sale in California
Material	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty			
Glass	Yes	Yes	cULus Classified - Damp Location Rated	<a href="#">5 Year Limited</a>			



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

