



S11916

18.5T8/LED/48-840/FF/BP 120-277V
18.5 watt T8 LED; 4000K; Medium Bi Pin base; 50000 Average rated hours; 120-277 Volts; Type B; Ballast Bypass; Double Ended Wiring



Features

- All glass tube
- Approved for use with tube guards
- NSF Approved
- No ballast or external driver required

*Existing wiring to both sockets can remain in place
*Will work on both shunted or non-shunted sockets

S11916

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Power Factor	Lamp Shape
S11916	045923119163	120-277	18.5	50/60Hz	32W	0.90	T8
Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Medium Bi-Pin	G13	18.5T8/LED/48-840/FF/BP 120-277V	Non-Dimmable	Frosted	48"	1.00"	2500
Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	THD	Pack
50000	4000	Cool White	80	180	-25C (-13F) to a maximum of +45C (+113F)		25
CEC Status	DLC ID:	Material	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty	
Lawful for sale in California	DLC ID:PLA9OZCCPT5Z DLC Search	Glass	Yes	Yes	cULus - Damp Location Rated	5 Year Limited	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

