

S16406

24T8/LED/HO-SIGN/60-840/BP 24W T8 LED; 4000K; 3100 Lumens; 120-277V; Type B; Single Ended; Ballast Bypass

Features

- Base rotates 90° for easy installation
 Direct wire 120-277V line voltage*
 NSF Approved
 No ballast or external driver required



Item N	Item Number		UPC		Voltage		Watt	ts	Operating Frequenc		Lamp Shape		В	ase	ANSI Base	
S10	S16406 045923164			064 120-27		0-277	24		50/60Hz		Т8		Recessed Double Contact HO/VHO		R17d	
	Lamp Code			Finish		MOL Inch			OD In nches	Initial Lumens			age Rated Hours	Kelvin Temp	Color	
24T8/LED/HO-SIGN/60 840/BP				Frosted		60	' 1		1.00"	3100		50000		4000	Cool White	
CRI	Ope	Operating Temperature				Pack	Packag	e Type CEC		Statu	s RoHS	6 Compliant	UL or ETL Listed			
83	33	0	-40C (-40F) to a maximum of +45C (+113F)				of	10	Sleeve		Lawful for sale in California			Yes	Yes	
	UL Classification													Warranty		
	cULus Classified - Damp Location Rated													5 Year Limited		



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051